

# PHILIPS LIGHTOLIER

## Downlighting

### Calculite LED gen 3 4" round tunable white

1000 & 1200lm



Calculite LED 4" generation 3 features industry leading visual comfort, excellent uniform illumination over time, and patented installation flexibility.

Complete product = Frame + Engine + Trim

Project: \_\_\_\_\_  
Location: \_\_\_\_\_  
Cat.No: \_\_\_\_\_  
Type: \_\_\_\_\_  
Lamps: \_\_\_\_\_ Qty: \_\_\_\_\_  
Notes: \_\_\_\_\_

#### Frame

example: C4RN

Series	Aperture	Installation	Voltage/ Options
<b>C4</b>	<b>R</b>		
<b>C4</b> Calculite LED 4" aperture	<b>R</b> Round	<b>N</b> New Construction <b>R</b> Remodeler	— Universal (120/277V) <b>3</b> 347V <b>EM</b> Emergency <sup>1,2</sup> <b>LC</b> Chicago Plenum <sup>1</sup>
		<b>A</b> Airseal IC	— Universal (120/277V)

#### Engine

example: C4L10865MDUTW

Series	Lumens	CRI	CCT	Beam	Dimming	Voltage	Options
<b>C4L</b>							<b>TW</b>
<b>C4L</b> Calculite LED 4" aperture	<b>10</b> 1000lm <b>12</b> 1200lm <sup>3</sup>	<b>8</b> 80 CRI	<b>65</b> 6500-2700K	<b>M</b> Medium (56°) <b>W</b> Wide (76°) <sup>4</sup>	<b>D</b> Dali	<b>U</b> Universal (120/277V/347V)	<b>TW</b> Tunable White

#### Trim

example: C4RDLCCP

Series	Aperture	Style	Finish	Flange
<b>C4</b>	<b>R</b>			
<b>C4</b> Calculite LED 4" aperture	<b>R</b> Round	<b>DL</b> Downlight <b>WW</b> Open Wall Wash <b>LW</b> Lensed Wall Wash <b>CW</b> Corner Wall Wash <sup>5</sup> <b>DW</b> Double Wall Wash <sup>5</sup>	<b>CL</b> Specular clear <b>CC</b> Comfort clear <b>CD</b> Comfort clear diffuse <b>CZ</b> Champagne bronze <b>BK</b> Black (matte) <b>WH</b> White (matte)	— White (matte) <b>P</b> Polished <b>F</b> Flangeless <sup>5</sup> — White (matte) <b>F</b> Flangeless <sup>5</sup>

#### Accessories (ordered with a flangeless trim)


**CA4RFT** Mud-in ring for use with flangeless installations.  
**CAEM** Field installable EM pack.  
**C4RVPWH** IP65 rated vandal proof matte white accessory that mounts onto a flangeless trim.

- Emergency (EM) and Chicago Plenum (LC) options are only available with New construction (N) installations.
- Emergency (EM) frame comes with emergency battery pack and ceiling mountable test switch. Reflector mounted test switch requires above ceiling access and is only available with the downlight option. For reflector mounted test switch, order emergency frame and add "EM" suffix to reflector (example: C4RDLCCEM).
- The 1200lm is only compatible with Airseal (C4RA or C4SA) frame.
- Wide (W) is ideal for wall washing applications.
- Corner (CW) and Double (DW) wall wash are not available with flangeless (F) option.


# C4RTW Calculite LED generation 3

4" round tunable white


## New Construction (N)




## Chicago Plenum (LC)




## Remodeler (R)



## Vandal Proof accessory (VP)



## Flangeless mud-in ring (CA4RFT)



Consult factory for wood installation instructions.

## Lifetime (TM-21) data

Lumens	Narrow beam	Medium/Wide beam*
500lm		
1000lm	L90 @ 60,000hrs.	L90 @ 60,000hrs.
1500lm		
2000lm		
2500lm	L90 @ 60,000hrs.	L85 @ 60,000hrs.
3000lm*		

\* Lutron 3000lm with Medium/Wide beam is L80 @ 60,000hrs.

# C4RTW Calculite LED generation 3

4" round tunable white

## Frame-in-kits

### New Construction

Galvanized stamped steel for dry or plaster ceilings. Preinstalled telescoping mounting bars from 13" to 24". For 4' distances, use 1/2" EMT, 1-1/2" x 1/2" U or C channel.

**Max ceiling thickness is 2".**

### AirSeal

Black painted steel housing for dry or plaster ceilings. Pre-installed telescoping mounting bars from 13" to 24".

### Patented install Mounting frame

With no driver attached, this versatile frame is independent of driver accommodating a wide range of lumen packages, driver types and CCTs, including 120V and 277V inputs.

Close-cut aperture design eliminates the possibility of undesired gap between ceiling opening and reflector flange.

Separate wiring compartment for wiring frame to building allows inspection prior to light engine installation.

Simple plug-and-play connection between the frame and light engine from below the ceiling eliminates the need for wiring between frame and LED driver, and also saves time during installation and future replacements/upgrades. Plug-and-play receptacle accommodates technology upgrade of light engines and replacements for the life of the building.

## Optical systems

### Comfort throughout the space

Patented optical system combines primary and secondary optics to provide a true 50° physical cutoff and 45° reflected cutoff virtually eliminating the view of the light source and bright spots in the reflector.

A new reflector curve reduces reflector brightness by up to 50% compared to existing products, allowing for the use of higher lumen packages in smaller apertures without creating bright spots in the ceiling.

### Quality of light

2 SDCM ensures color consistency from fixture to fixture and over the luminaire's long lifetime.

Proprietary optical grade silicone lens with patterned surface provides soft, even beam diffusion without hotspots or dark rings.

## Light Engine

Quick connect power pack comprised of light source and driver allow for easy installation and replacement from below ceiling with no need for additional wiring. This allows for

- Frame and ceiling installation to be performed while still finalizing details such as lumen packages, CCT and control type.
- Easy replacement of electronics at end of life with minimal wasted material and labor required.
- Ease and upgradability of technology.

## Drivers

- EldoLED ECoDrive Dali 1% Dimming

## Options and Accessories

**Flangeless mud-in ring:** Use **CA4RFT** for use with flangeless installations.

**Sloped ceilings:** Compatible with sloped ceiling adapters (see **SCA** spec sheet).

## Labels and Listings

cULus listed for wet locations

IBEW Union made (light engines & reflectors)

RoHS compliant


## Warranty

5 year warranty on complete system.

Complete warranty available at: [http://images.philips.com/is/content/PhilipsConsumer/PDFDownloads/United%20States/ODLI20150930\\_003-UPD-en\\_US-Philips-warranty-indoor-PLS-us.pdf](http://images.philips.com/is/content/PhilipsConsumer/PDFDownloads/United%20States/ODLI20150930_003-UPD-en_US-Philips-warranty-indoor-PLS-us.pdf)

## Color information

4" 1000lm	2700K	3000K	3500K	4000K	5000K	6500K
Flux (lms)	909	920	942	951	927	927
Power (W)	10.24	10.24	10.22	10.19	9.94	9.98
Efficacy (lm/W)	88.8	89.8	92.2	93.4	93.3	92.8
CCT	2766	2974	3423	3933	4866	6458
CRI	86	87	88	89	87	83
R9	21	26	33	36	32	13
x	0.4513	0.4335	0.404	0.3797	0.3483	0.3136
y	0.4034	0.394	0.3783	0.3653	0.3483	0.3288
Duv	-0.0019	-0.0036	-0.0053	-0.0052	-0.0029	0.0026




# C4RTW Calculite LED generation 3

4" round tunable white

## Medium beam, 1000lm Engine, 88.8 lm/W

Candela Curve



Frame: **C4RN**  
Engine: **C4L10865MDUTW**  
Trim: **C4RDLCL**

Output lumens: 909.5 lms  
Input watts: 10.2 W  
CRI: 80 min  
CCT<sup>1</sup>: 2700K  
Spacing Crit.: 0.8  
Beam Angle: 52°

Zonal summary

Zone	Lumens	%Luminaire
0-30	732	80.5%
0-40	863	94.9%
0-60	905	99.6%
0-90	909	100.0%

Angle	Mean CP	Lumens
0	1060	
5	1063	103
10	1103	
15	1112	307
20	992	
25	726	323
30	405	
35	190	131
40	99	
45	48	38
50	10	
55	5	5
60	3	
65	2	2
70	2	
75	1	1
80	1	
85	1	0
90	0	

Single unit data

Height to lighted plane	Initial center beam foot-candles	Beam diameter (ft)*
5'	42	4.0'
6'	29	4.8'
7'	22	5.6'
8'	17	6.4'
9'	13	7.2'

\* Beam diameter is where foot-candles drop to 50% of maximum.

Multiple unit data - RCR 2

Spacing on center	Initial center beam foot-candles	Watts per sq. ft.
5'	41.8	0.45
6'	27.5	0.30
7'	19.6	0.21
8'	16.3	0.18
9'	13.1	0.14

38' x 38' x 10' Room, Workplane 2.5'  
above floor, 80/50/20% Reflectances

**Efficacy: 88.8 lm/w**  
Report<sup>2</sup>: 1215GFR

Adjustment factors


Finish	CCT	Lumens
CL = 100%	80CRI 4000K = 103%	1500lm = ???%
CC = 95%	80CRI 3500K = 100%	1000lm = 100%
CD = 87%	80CRI 3000K = 95%	
CZ = 63%	80CRI 2700K = 93%	
WH = 87%	90CRI 3000K = 83%	
BK = 57%	90CRI 2700K = 78%	

Coefficients of utilization

Ceiling	80%				70%				50%				30%				0%
Wall	70	50	30	10	50	10	50	10	50	10	50	10	50	10	50	10	0
RCR	Zonal cavity method - Effective floor reflectance = 20%																
Room Cavity Ratio	0	119	119	119	119	116	116	111	111	106	106	100	100	106	106	100	100
1	114	111	109	107	109	105	105	105	102	101	99	94	94	96	92	88	88
2	109	104	100	97	102	96	96	99	94	96	94	88	88	91	86	83	83
3	104	97	93	89	96	88	88	94	87	91	86	80	78	86	80	78	78
4	99	92	86	82	90	82	82	88	81	86	80	73	73	82	75	73	73
5	94	86	81	77	85	76	76	84	76	82	75	69	69	78	71	69	69
6	90	81	76	72	81	71	71	79	71	78	71	63	63	74	66	65	65
7	86	77	71	67	76	67	67	75	67	74	66	59	59	70	63	61	61
8	82	73	67	63	72	63	63	71	63	70	63	57	57	67	59	58	58
9	78	69	64	60	69	60	60	68	60	67	59	53	53	64	56	55	55
10	75	66	60	57	65	56	56	64	56	64	56	50	50	61	53	52	52

## Wide beam, 1200lm Engine, 81.7 lm/W

Candela Curve



Frame: **C4RN**  
Engine: **C4L12865WDUTW**  
Trim: **C4RDLCL**

Output lumens: 837 lms  
Input watts: 10.2 W  
CRI: 80 min  
CCT<sup>1</sup>: 2700K  
Spacing Crit.: 1.1  
Beam Angle: 72°

Zonal summary

Zone	Lumens	%Luminaire
0-30	519	62.0%
0-40	750	89.6%
0-60	833	99.5%
0-90	837	100.0%

Angle	Mean CP	Lumens
0	557	
5	563	55
10	603	
15	654	184
20	663	
25	622	280
30	516	
35	370	231
40	233	
45	87	76
50	15	
55	8	7
60	4	
65	3	3
70	2	
75	1	1
80	1	
85	0	0
90	0	

Single unit data

Height to lighted plane	Initial center beam foot-candles	Beam diameter (ft)*
5'	22	5.5'
6'	15	6.6'
7'	11	7.7'
8'	9	8.8'
9'	7	9.9'

\* Beam diameter is where foot-candles drop to 50% of maximum.

Multiple unit data - RCR 2

Spacing on center	Initial center beam foot-candles	Watts per sq. ft.
5'	37.7	0.45
6'	24.8	0.30
7'	17.7	0.21
8'	14.7	0.18
9'	11.8	0.14

38' x 38' x 10' Room, Workplane 2.5'  
above floor, 80/50/20% Reflectances

**Efficacy: 81.7 lm/w**  
Report<sup>2</sup>: 1216GFR

Adjustment factors

Finish	CCT	Lumens
CL = 100%	80CRI 4000K = 102%	1500lm = ???%
CC = 95%	80CRI 3500K = 100%	1000lm = 100%
CD = 87%	80CRI 3000K = 97%	
CZ = 63%	80CRI 2700K = 87%	
WH = 87%	90CRI 3000K = 77%	
BK = 57%	90CRI 2700K = 73%	

Coefficients of utilization

Ceiling	80%				70%				50%				30%				0%
Wall	70	50	30	10	50	10	50	10	50	10	50	10	50	10	50	10	0
RCR	Zonal cavity method - Effective floor reflectance = 20%																
Room Cavity Ratio	0	119	119	119	119	116	116	111	111	106	106	100	100	106	106	100	100
1	113	110	108	105	108	104	104	104	100	100	97	93	94	94	89	85	85
2	107	102	98	94	100	93	93	97	91	94	89	85	88	88	81	79	79
3	101	94	89	85	93	84	84	90	83	88	81	75	75	82	75	72	72
4	95	87	81	77	86	77	77	84	76	82	75	69	69	77	69	67	67
5	90	81	75	70	80	70	70	78	69	77	69	63	63	70	63	61	61
6	85	75	69	64	75	64	64	73	64	72	63	57	57	67	59	57	57
7	80	70	64	59	70	59	59	68	59	67	59	53	53	63	54	53	53
8	76	66	59	55	65	55	55	64	54	63	54	49	49	60	51	50	50
9	72	61	55	51	61	51	51	60	51	59	50	45	45	57	49	48	48
10	68	58	51	47	57	47	47	56	47	56	47	42	42	53	45	44	44

1. Correlated Color Temperature within specs as defined in ANSI\_NEMA\_ANSI C78.377-2008: Specifications for the Chromaticity of Solid State Lighting Products.
2. Tested using absolute photometry as specified in LM79: IESNA Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products.

© 2017 Philips Lighting Holding B.V. All rights reserved.  
Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.  
philips.com/luminaires



Philips Lighting, North America Corporation  
200 Franklin Square Drive, Somerset, NJ 08873  
Tel. 855-486-2216

Philips Lighting Canada Ltd.  
281 Hillmount Rd, Markham, ON, Canada L6C 2S3  
Tel. 800-668-9008