



The most reliable!

MASTER PL-L 4 Pin

MASTER PL-L is a medium to high-wattage linear compact fluorescent lamp, typically used for general-illumination ceiling luminaires in retail, hospitality and office applications demanding higher lighting levels. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. It is designed for operation on electromagnetic as well as electronic HF control gear and is provided with a plug-in/pull-out lamp base.

Benefits

Features

Application

Warnings and Safety

Versions



18W, 2G11, 4P



24W, 2G11, 4P



36W, 2G11, 4P



PL-L 2G11 4P

MASTER PL-L 4 Pin

Versions



40W, 2G11, 4P




55W, 2G11, 4P



80W, 2G11, 4P


Dimensional drawing



Product					
MASTER PL-L 18W/827/4P 1CT/25					
MASTER PL-L 36W/865/4P 1CT/25					
MASTER PL-L 36W/840/4P 1CT/25					
MASTER PL-L 55W/840/4P 1CT/25					
MASTER PL-L 55W/865/4P 1CT/25					
MASTER PL-L 24W/865/4P 1CT/25_APR	39.0	18.0	289.2	315	321.6
	mm	mm	mm	mm	mm
MASTER PL-L 18W/865/4P 1CT/25	39.0	18.0	194.2	220	226.6
	mm	mm	mm	mm	mm
MASTER PL-L 80W/840/4P 1CT/25					
MASTER PL-L 80W/830/4P 1CT/25					
MASTER PL-L 55W/865/4P 1CT/25					
MASTER PL-L 55W/840/4P 1CT/25					
MASTER PL-L 55W/830/4P 1CT/25					
MASTER PL-L 40W/840/4P 1CT/25					
MASTER PL-L 40W/830/4P 1CT/25					
MASTER PL-L 36W/865/4P 1CT/25					
MASTER PL-L 36W/840/4P 1CT/25					
MASTER PL-L 36W/830/4P 1CT/25					
MASTER PL-L 36W/827/4P 1CT/25					
MASTER PL-L 24W/865/4P 1CT/25					
MASTER PL-L 24W/840/4P 1CT/25					
MASTER PL-L 24W/830/4P 1CT/25					
MASTER PL-L 24W/827/4P 1CT/25					
MASTER PL-L 18W/865/4P 1CT/25					
MASTER PL-L 18W/840/4P 1CT/25					
MASTER PL-L 18W/830/4P 1CT/25					

MASTER PL-L 4 Pin

Dimensional drawing



Product

MASTER PL-L 32W/865/4P 1CT/25

Approval and Application

Mercury (Hg) Content (Nom) 2.0 mg

Controls and Dimming

Dimmable Yes

General Information

Cap-Base 2G11

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Energy Efficiency Label (EEL)
927903008270	MASTER PL-L 18W/827/4P 1CT/25	20 kWh	A
927903008370	MASTER PL-L 18W/830/4P 1CT/25	20 kWh	A
927903008470	MASTER PL-L 18W/840/4P 1CT/25	20 kWh	A
927903086572	MASTER PL-L 18W/865/4P 1CT/25	20 kWh	A
927903086578	MASTER PL-L 18W/865/4P 1CT/25	20 kWh	A
927903208270	MASTER PL-L 24W/827/4P 1CT/25	26 kWh	A
927903208370	MASTER PL-L 24W/830/4P 1CT/25	26 kWh	A
927903208470	MASTER PL-L 24W/840/4P 1CT/25	26 kWh	A
927903286570	MASTER PL-L 24W/865/4P 1CT/25	26 kWh	A
927903286572	MASTER PL-L 24W/865/4P 1CT/25_APR	26 kWh	A
927903408270	MASTER PL-L 36W/827/4P 1CT/25	40 kWh	A
927903408370	MASTER PL-L 36W/830/4P 1CT/25	40 kWh	A

Order Code	Full Product Name	Energy Consumption kWh/1000 h	Energy Efficiency Label (EEL)
927903408470	MASTER PL-L 36W/840/4P 1CT/25	40 kWh	A
927903408472	MASTER PL-L 36W/840/4P 1CT/25	40 kWh	A
927903486570	MASTER PL-L 36W/865/4P 1CT/25	40 kWh	A
927903486572	MASTER PL-L 36W/865/4P 1CT/25	40 kWh	A
927907986501	MASTER PL-L 32W/865/4P 1CT/25	-	A
927908208370	MASTER PL-L 40W/830/4P 1CT/25	44 kWh	A+
927908208470	MASTER PL-L 40W/840/4P 1CT/25	44 kWh	A+
927908708370	MASTER PL-L 55W/830/4P 1CT/25	61 kWh	A
927908708470	MASTER PL-L 55W/840/4P 1CT/25	61 kWh	A
927908708472	MASTER PL-L 55W/840/4P 1CT/25	61 kWh	A
927908786570	MASTER PL-L 55W/865/4P 1CT/25	61 kWh	A
927908786572	MASTER PL-L 55W/865/4P 1CT/25	61 kWh	A

MASTER PL-L 4 Pin

Order Code	Full Product Name	Energy	Energy
		Consumption kWh/ 1000 h	Efficiency Label (EEL)
927909583070	MASTER PL-L 80W/830/4P 1CT/25	88 kWh	A

Order Code	Full Product Name	Energy	Energy
		Consumption kWh/ 1000 h	Efficiency Label (EEL)
927909584070	MASTER PL-L 80W/840/4P 1CT/25	88 kWh	A

Operating and Electrical

Order Code	Full Product Name	Lamp	Voltage (Nom)	Power
		Current (Nom)		(Rated) (Nom)
927903008270	MASTER PL-L 18W/827/4P 1CT/25	0.375 A	-	18.0 W
927903008370	MASTER PL-L 18W/830/4P 1CT/25	0.375 A	-	18.0 W
927903008470	MASTER PL-L 18W/840/4P 1CT/25	0.375 A	-	18.0 W
927903086572	MASTER PL-L 18W/865/4P 1CT/25	0.375 A	-	18.0 W
927903086578	MASTER PL-L 18W/865/4P 1CT/25	0.375 A	-	18.0 W
927903208270	MASTER PL-L 24W/827/4P 1CT/25	0.345 A	-	24.0 W
927903208370	MASTER PL-L 24W/830/4P 1CT/25	0.345 A	-	24.0 W
927903208470	MASTER PL-L 24W/840/4P 1CT/25	0.345 A	-	24.0 W
927903286570	MASTER PL-L 24W/865/4P 1CT/25	0.345 A	-	24.0 W
927903286572	MASTER PL-L 24W/865/4P 1CT/25_APR	0.345 A	-	24.0 W
927903408270	MASTER PL-L 36W/827/4P 1CT/25	0.435 A	-	36.0 W
927903408370	MASTER PL-L 36W/830/4P 1CT/25	0.435 A	-	36 W
927903408470	MASTER PL-L 36W/840/4P 1CT/25	0.435 A	-	36.0 W

Order Code	Full Product Name	Lamp	Voltage (Nom)	Power
		Current (Nom)		(Rated) (Nom)
927903408472	MASTER PL-L 36W/840/4P 1CT/25	0.435 A	-	36.0 W
927903486570	MASTER PL-L 36W/865/4P 1CT/25	0.435 A	-	36 W
927903486572	MASTER PL-L 36W/865/4P 1CT/25	0.435 A	-	36 W
927907986501	MASTER PL-L 32W/865/4P 1CT/25	0.32 A	95 V	31 W
927908208370	MASTER PL-L 40W/830/4P 1CT/25	0.320 A	-	40.0 W
927908208470	MASTER PL-L 40W/840/4P 1CT/25	0.320 A	-	40 W
927908708370	MASTER PL-L 55W/830/4P 1CT/25	0.525 A	-	55 W
927908708470	MASTER PL-L 55W/840/4P 1CT/25	0.525 A	-	55.0 W
927908708472	MASTER PL-L 55W/840/4P 1CT/25	0.525 A	-	55.0 W
927908786570	MASTER PL-L 55W/865/4P 1CT/25	0.525 A	-	55.0 W
927908786572	MASTER PL-L 55W/865/4P 1CT/25	0.525 A	-	55.0 W
927909583070	MASTER PL-L 80W/830/4P 1CT/25	0.555 A	-	80 W
927909584070	MASTER PL-L 80W/840/4P 1CT/25	0.555 A	-	80.0 W

General Information (1/2)

Order Code	Full Product Name	Life To 50%						
		Failures Preheat (Nom)	Life To 10% Failures (Nom)	Life To 50% Failures (Nom)	LSF 12000 h Rated	LSF Preheat 16000 h Rated	LSF 2000 h Rated	LSF Preheat 20000 h Rated
927903008270	MASTER PL-L 18W/827/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903008370	MASTER PL-L 18W/830/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903008470	MASTER PL-L 18W/840/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903086572	MASTER PL-L 18W/865/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903086578	MASTER PL-L 18W/865/4P 1CT/25	0 h	0 h	15000 h	80 %	82 %	99 %	50 %
927903208270	MASTER PL-L 24W/827/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903208370	MASTER PL-L 24W/830/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903208470	MASTER PL-L 24W/840/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903286570	MASTER PL-L 24W/865/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %

MASTER PL-L 4 Pin

Order Code	Full Product Name	Life To 50%						
		Failures Preheat (Nom)	Life To 10% Failures (Nom)	Life To 50% Failures (Nom)	LSF 12000 h Rated	LSF Preheat 16000 h Rated	LSF 2000 h Rated	LSF Preheat 20000 h Rated
927903286572	MASTER PL-L 24W/865/4P 1CT/25_APR	0 h	0 h	15000 h	80 %	82 %	99 %	50 %
927903408270	MASTER PL-L 36W/827/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903408370	MASTER PL-L 36W/830/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903408470	MASTER PL-L 36W/840/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903408472	MASTER PL-L 36W/840/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903486570	MASTER PL-L 36W/865/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927903486572	MASTER PL-L 36W/865/4P 1CT/25	20000 h	10000 h	15000 h	80 %	82 %	99 %	50 %
927907986501	MASTER PL-L 32W/865/4P 1CT/25	12000 h	-	-	-	-	-	-
927908208370	MASTER PL-L 40W/830/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %
927908208470	MASTER PL-L 40W/840/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %
927908708370	MASTER PL-L 55W/830/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %
927908708470	MASTER PL-L 55W/840/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %
927908708472	MASTER PL-L 55W/840/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %
927908786570	MASTER PL-L 55W/865/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %
927908786572	MASTER PL-L 55W/865/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %
927909583070	MASTER PL-L 80W/830/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %
927909584070	MASTER PL-L 80W/840/4P 1CT/25	20000 h	-	-	-	82 %	-	50 %

General Information (2/2)

Order Code	Full Product Name	LSF Preheat	LSF 4000 h	LSF Preheat	LSF 6000 h	LSF Preheat	LSF 8000 h	LSF Preheat	System
		2000 h Rated	Rated	4000 h Rated	Rated	6000 h Rated	Rated	8000 h Rated	Description
927903008270	MASTER PL-L 18W/827/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903008370	MASTER PL-L 18W/830/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903008470	MASTER PL-L 18W/840/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903086572	MASTER PL-L 18W/865/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903086578	MASTER PL-L 18W/865/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903208270	MASTER PL-L 24W/827/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903208370	MASTER PL-L 24W/830/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903208470	MASTER PL-L 24W/840/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903286570	MASTER PL-L 24W/865/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903286572	MASTER PL-L 24W/865/4P 1CT/25_APR	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903408270	MASTER PL-L 36W/827/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903408370	MASTER PL-L 36W/830/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903408470	MASTER PL-L 36W/840/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903408472	MASTER PL-L 36W/840/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903486570	MASTER PL-L 36W/865/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927903486572	MASTER PL-L 36W/865/4P 1CT/25	99 %	98 %	99 %	96 %	98 %	94 %	97 %	-
927907986501	MASTER PL-L 32W/865/4P 1CT/25	-	-	-	-	-	-	-	-

MASTER PL-L 4 Pin

Order Code	Full Product Name	LSF Preheat 2000 h Rated	LSF 4000 h Rated	LSF Preheat 4000 h Rated	LSF 6000 h Rated	LSF Preheat 6000 h Rated	LSF 8000 h Rated	LSF Preheat 8000 h Rated	System Description
927908208370	MASTER PL-L 40W/830/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency
927908208470	MASTER PL-L 40W/840/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency
927908708370	MASTER PL-L 55W/830/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency
927908708470	MASTER PL-L 55W/840/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency
927908708472	MASTER PL-L 55W/840/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency
927908786570	MASTER PL-L 55W/865/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency
927908786572	MASTER PL-L 55W/865/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency
927909583070	MASTER PL-L 80W/830/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency
927909584070	MASTER PL-L 80W/840/4P 1CT/25	99 %	-	99 %	-	98 %	-	97 %	High Frequency

Light Technical (1/2)

Order Code	Full Product Name	Color		Correlated Color Temperature (Nom)	Color			
		Code	Color Designation		Rendering Index (Nom)	LLMF 12000 h Rated	LLMF 16000 h Rated	LLMF 2000 h Rated
927903008270	MASTER PL-L 18W/827/4P 1CT/25	827	Incandescent White	2700 K	82	90 %	90 %	94 %
927903008370	MASTER PL-L 18W/830/4P 1CT/25	830	Warm White (WW)	3000 K	>80	90 %	90 %	94 %
927903008470	MASTER PL-L 18W/840/4P 1CT/25	840	Cool White (CW)	4000 K	82	90 %	90 %	94 %
927903086572	MASTER PL-L 18W/865/4P 1CT/25	865	Cool Daylight	6500 K	80	87 %	88 %	93 %
927903086578	MASTER PL-L 18W/865/4P 1CT/25	865	Cool Daylight	6500 K	80	87 %	88 %	93 %
927903208270	MASTER PL-L 24W/827/4P 1CT/25	827	Incandescent White	2700 K	82	90 %	90 %	94 %
927903208370	MASTER PL-L 24W/830/4P 1CT/25	830	Warm White (WW)	3000 K	>80	90 %	90 %	94 %
927903208470	MASTER PL-L 24W/840/4P 1CT/25	840	Cool White (CW)	4000 K	82	90 %	90 %	94 %
927903286570	MASTER PL-L 24W/865/4P 1CT/25	865	Cool Daylight	6500 K	80	87 %	88 %	93 %
927903286572	MASTER PL-L 24W/865/4P 1CT/ 25_APR	865	Cool Daylight	6500 K	80	87 %	88 %	93 %
927903408270	MASTER PL-L 36W/827/4P 1CT/25	827	Incandescent White	2700 K	82	90 %	90 %	94 %
927903408370	MASTER PL-L 36W/830/4P 1CT/25	830	Warm White (WW)	3000 K	>80	90 %	90 %	94 %
927903408470	MASTER PL-L 36W/840/4P 1CT/25	840	Cool White (CW)	4000 K	82	90 %	90 %	94 %
927903408472	MASTER PL-L 36W/840/4P 1CT/25	840	Cool White (CW)	4100 K	82	90 %	90 %	94 %
927903486570	MASTER PL-L 36W/865/4P 1CT/25	865	Cool Daylight	6500 K	80	87 %	88 %	93 %
927903486572	MASTER PL-L 36W/865/4P 1CT/25	865	Cool Daylight	6500 K	80	87 %	88 %	93 %
927907986501	MASTER PL-L 32W/865/4P 1CT/25	865	Cool Daylight	6500 K	79	-	-	-
927908208370	MASTER PL-L 40W/830/4P 1CT/25	830	Warm White (WW)	3000 K	>80	91 %	90 %	95 %
927908208470	MASTER PL-L 40W/840/4P 1CT/25	840	Cool White (CW)	4000 K	82	91 %	90 %	95 %
927908708370	MASTER PL-L 55W/830/4P 1CT/25	830	Warm White (WW)	3000 K	>80	91 %	90 %	95 %
927908708470	MASTER PL-L 55W/840/4P 1CT/25	840	Cool White (CW)	4000 K	82	91 %	90 %	95 %
927908708472	MASTER PL-L 55W/840/4P 1CT/25	840	Cool White (CW)	4000 K	82	91 %	90 %	95 %
927908786570	MASTER PL-L 55W/865/4P 1CT/25	865	Cool Daylight	6500 K	80	90 %	88 %	94 %
927908786572	MASTER PL-L 55W/865/4P 1CT/25	865	Cool Daylight	6500 K	80	90 %	88 %	94 %
927909583070	MASTER PL-L 80W/830/4P 1CT/25	830	Warm White (WW)	3000 K	>80	91 %	90 %	95 %
927909584070	MASTER PL-L 80W/840/4P 1CT/25	840	Cool White (CW)	4000 K	82	91 %	90 %	95 %

MASTER PL-L 4 Pin

Light Technical (2/2)

Order Code	Full Product Name	LLMF	LLMF	LLMF	LLMF	Lumen	Lumen	Luminous	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
		20000 h Rated	4000 h Rated	6000 h Rated	8000 h Rated	Maintenance 2000 h (Nom)	Maintenance 5000 h (Nom)	Efficacy (rated) (Nom)		
927903008270	MASTER PL-L 18W/ 827/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	67 lm/W	1200 lm	1200 lm
927903008370	MASTER PL-L 18W/ 830/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	67 lm/W	1200 lm	1200 lm
927903008470	MASTER PL-L 18W/ 840/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	67 lm/W	1200 lm	1200 lm
927903086572	MASTER PL-L 18W/ 865/4P 1CT/25	87 %	91 %	90 %	89 %	-	-	65 lm/W	1200 lm	1170 lm
927903086578	MASTER PL-L 18W/ 865/4P 1CT/25	87 %	91 %	90 %	89 %	-	-	65 lm/W	1200 lm	1170 lm
927903208270	MASTER PL-L 24W/ 827/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	75 lm/W	1800 lm	1800 lm
927903208370	MASTER PL-L 24W/ 830/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	75 lm/W	1800 lm	1800 lm
927903208470	MASTER PL-L 24W/ 840/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	75 lm/W	1800 lm	1800 lm
927903286570	MASTER PL-L 24W/ 865/4P 1CT/25	87 %	91 %	90 %	89 %	-	-	73 lm/W	1800 lm	1750 lm
927903286572	MASTER PL-L 24W/ 865/4P 1CT/25_APR	87 %	91 %	90 %	89 %	-	-	73 lm/W	1800 lm	1750 lm
927903408270	MASTER PL-L 36W/ 827/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	81 lm/W	2900 lm	2900 lm
927903408370	MASTER PL-L 36W/ 830/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	81 lm/W	2900 lm	2900 lm
927903408470	MASTER PL-L 36W/ 840/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	81 lm/W	2900 lm	2900 lm
927903408472	MASTER PL-L 36W/ 840/4P 1CT/25	90 %	93 %	92 %	91 %	-	-	81 lm/W	2900 lm	2900 lm
927903486570	MASTER PL-L 36W/ 865/4P 1CT/25	87 %	91 %	90 %	89 %	-	-	80 lm/W	2900 lm	2880 lm
927903486572	MASTER PL-L 36W/ 865/4P 1CT/25	87 %	91 %	90 %	89 %	-	-	80 lm/W	2900 lm	2880 lm
927907986501	MASTER PL-L 32W/ 865/4P 1CT/25	-	-	-	-	85 %	80 %	91.9 lm/W	2850 lm	-
927908208370	MASTER PL-L 40W/ 830/4P 1CT/25	90 %	94 %	93 %	92 %	-	-	88 lm/W	3500 lm	3500 lm
927908208470	MASTER PL-L 40W/ 840/4P 1CT/25	90 %	94 %	93 %	92 %	-	-	88 lm/W	3500 lm	3500 lm
927908708370	MASTER PL-L 55W/ 830/4P 1CT/25	90 %	94 %	93 %	92 %	-	-	87 lm/W	4800 lm	4800 lm
927908708470	MASTER PL-L 55W/ 840/4P 1CT/25	90 %	94 %	93 %	92 %	-	-	87 lm/W	4800 lm	4800 lm
927908708472	MASTER PL-L 55W/ 840/4P 1CT/25	90 %	94 %	93 %	92 %	-	-	87 lm/W	4800 lm	4800 lm
927908786570	MASTER PL-L 55W/ 865/4P 1CT/25	87 %	93 %	92 %	91 %	-	-	82 lm/W	4600 lm	4800 lm
927908786572	MASTER PL-L 55W/ 865/4P 1CT/25	87 %	93 %	92 %	91 %	-	-	82 lm/W	4600 lm	4800 lm

MASTER PL-L 4 Pin

Order Code	Full Product Name	LLMF	LLMF	LLMF	LLMF	Lumen	Lumen	Luminous	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
		20000 h Rated	4000 h Rated	6000 h Rated	8000 h Rated	Maintenance 2000 h (Nom)	Maintenance 5000 h (Nom)	Efficacy (rated) (Nom)		
927909583070	MASTER PL-L 80W/830/4P 1CT/25	90 %	94 %	93 %	92 %	-	-	75 lm/W	6000 lm	6000 lm
927909584070	MASTER PL-L 80W/840/4P 1CT/25	90 %	94 %	93 %	92 %	-	-	75 lm/W	6000 lm	6000 lm

Temperature

Order Code	Full Product Name	Design Temperature (Nom)	Order Code	Full Product Name	Design Temperature (Nom)
927903008270	MASTER PL-L 18W/827/4P 1CT/25	30 °C	927903408472	MASTER PL-L 36W/840/4P 1CT/25	30 °C
927903008370	MASTER PL-L 18W/830/4P 1CT/25	30 °C	927903486570	MASTER PL-L 36W/865/4P 1CT/25	30 °C
927903008470	MASTER PL-L 18W/840/4P 1CT/25	30 °C	927903486572	MASTER PL-L 36W/865/4P 1CT/25	30 °C
927903086572	MASTER PL-L 18W/865/4P 1CT/25	30 °C	927907986501	MASTER PL-L 32W/865/4P 1CT/25	-
927903086578	MASTER PL-L 18W/865/4P 1CT/25	30 °C	927908208370	MASTER PL-L 40W/830/4P 1CT/25	30 °C
927903208270	MASTER PL-L 24W/827/4P 1CT/25	30 °C	927908208470	MASTER PL-L 40W/840/4P 1CT/25	30 °C
927903208370	MASTER PL-L 24W/830/4P 1CT/25	30 °C	927908708370	MASTER PL-L 55W/830/4P 1CT/25	30 °C
927903208470	MASTER PL-L 24W/840/4P 1CT/25	30 °C	927908708470	MASTER PL-L 55W/840/4P 1CT/25	30 °C
927903286570	MASTER PL-L 24W/865/4P 1CT/25	30 °C	927908708472	MASTER PL-L 55W/840/4P 1CT/25	30 °C
927903286572	MASTER PL-L 24W/865/4P 1CT/25_APR	30 °C	927908786570	MASTER PL-L 55W/865/4P 1CT/25	30 °C
927903408270	MASTER PL-L 36W/827/4P 1CT/25	30 °C	927908786572	MASTER PL-L 55W/865/4P 1CT/25	30 °C
927903408370	MASTER PL-L 36W/830/4P 1CT/25	30 °C	927909583070	MASTER PL-L 80W/830/4P 1CT/25	30 °C
927903408470	MASTER PL-L 36W/840/4P 1CT/25	30 °C	927909584070	MASTER PL-L 80W/840/4P 1CT/25	30 °C

