



Energy efficiency and long life

Ceramalux Instant Restrike

Dual arc-tube delivers 40,000 hour rated average life as compared to 24,000 hour rated average life for standard HPS lamps. Ideal for industrial applications, warehouses, post top applications and parking lots.

Benefits

- Rated Average Life 24,000+ Hours*
- For applications where instant restrike is not required, rated average Life is 40,000 Hours.
- * Rated average life is the life obtained, on the average, from large representative groups of lamps in laboratory tests under controlled conditions at 10 or more operating hours per start. It is based on survival of at least 67% of the lamps and allows for individual lamps or groups of lamps to vary considerably from the average

Features

- Extra ArcTube Offers Light Instantly after momentary power Interruption and will provide 80% light output within 1–2 Minutes.
- Operates on standard HPS ballasts and auxiliary equipments.
- Available in 250, and 400 Watt ED18 mogul base / Available in 50, 70, 100, and 150 Watt, ED 23-1/2 mogul base / Available in 1000 Watts E-25 mogul base.

Application

- Ideal for security lighting, roadway lighting, warehouse lighting, and industrial applications.

Warnings and Safety

- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050


Ceramalux Instant Restrike

Versions




400 W Single Contact Mogul
Screw ED-18 Clear

Dimensional drawing



Product	D	C (max)
37688-9 400W C400S51/2 Dual Arc Hp Lamp	2.25 in	9.75 in
C250S50/2 12PK	2.25 in	9.75 in



Product	D	C (max)
C150S55/2 12PK	2.938 in	7.75 in
C100S54/2 12PK	2.938 in	7.75 in

Ceramalux Instant Restrike

Operating and electrical	
Re-ignition Time (Min) (Max)	1 s
General information	
Cap-Base	E39
Main Application	General and Street Lighting
Operating Position	Universal
Luminaire design requirements	
Bulb Temperature (Max)	752 °F
Light technical	
Correlated Color Temperature (Nom)	2100 K
Color Rendering Index (Nom)	21
Mechanical and housing	
Bulb Finish	Clear
Bulb Material	Hard Glass

Approval and application

Order Code	Full Product Name	Mercury (Hg) Content (Max)	Mercury (Hg) Content (Nom)
376889	C400S51/2 12PK	-	47 mg
377176	C250S50/2 12PK	-	47 mg
265611	C150S55/2 12PK	34 mg	-
265603	C100S54/2 12PK	44.4 mg	-

Operating and electrical (1/2)

Order Code	Full Product Name	Lamp			
		Current (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
376889	C400S51/2 12PK	4.6 A	115 V	84 V	100 V
377176	C250S50/2 12PK	3 A	120 V	90 V	100 V

Order Code	Full Product Name	Lamp			
		Current (Nom)	Voltage (Max)	Voltage (Min)	Voltage (Nom)
265611	C150S55/2 12PK	3.2 A	62 V	48 V	55 V
265603	C100S54/2 12PK	2.1 A	62 V	45 V	55 V

Operating and electrical (2/2)

Order Code	Full Product Name	Power (Nom)
376889	C400S51/2 12PK	401.5 W
377176	C250S50/2 12PK	251 W

Order Code	Full Product Name	Power (Nom)
265611	C150S55/2 12PK	150.6 W
265603	C100S54/2 12PK	100.4 W

Light technical (1/2)

Order Code	Full Product Name	Chromaticity Coordinate X (Nom)	Chromaticity Coordinate Y (Nom)	Luminous Efficacy (rated) (Min)	Luminous Efficacy (rated) (Nom)
376889	C400S51/2 12PK	515	418	112.5 lm/W	125 lm/W
377176	C250S50/2 12PK	521	415	102.6 lm/W	114 lm/W

Order Code	Full Product Name	Chromaticity Coordinate X (Nom)	Chromaticity Coordinate Y (Nom)	Luminous Efficacy (rated) (Min)	Luminous Efficacy (rated) (Nom)
265611	C150S55/2 12PK	514	424	96 lm/W	106 lm/W
265603	C100S54/2 12PK	520	420	84 lm/W	93 lm/W

Light technical (2/2)

Order Code	Full Product Name	Design Mean Lumens	Luminous Flux (Rated) (Min)	Luminous Flux (Rated) (Nom)
376889	C400S51/2 12PK	44000 lm	45000 lm	50000 lm
377176	C250S50/2 12PK	24750 lm	25650 lm	28500 lm

Order Code	Full Product Name	Design Mean Lumens	Luminous Flux (Rated) (Min)	Luminous Flux (Rated) (Nom)
265611	C150S55/2 12PK	14000 lm	14400 lm	16000 lm
265603	C100S54/2 12PK	8190 lm	8400 lm	9300 lm

Mechanical and housing

Ceramalux Instant Restrike

Order Code	Full Product Name	Bulb Shape
376889	C400S51/2 12PK	ED18
377176	C250S50/2 12PK	ED18

Order Code	Full Product Name	Bulb Shape
265611	C150S55/2 12PK	ED-23 1/2
265603	C100S54/2 12PK	ED-23 1/2

