



Xtreme drivers for maximum energy savings

DynaVision Programmable Xtreme for CPO

Highly reliable and flexible electronic drivers for CPO lamps; designed to save on energy costs via integrated controls and to reduce maintenance costs thanks to 80,000-hour lifetime and integrated lightning protection. The DynaVision Programmable product family is the perfect basis for any sort of lighting management solution.

Benefits

- Enables 2-way communication with the lighting network (via DALI)
- Minimises maintenance cost due to the Xtreme lifetime of 80,000 hours and the integrated lightning protection
- Together with the CPO lamp the driver creates the most efficient white-light system in the industry in its power range

Features

- Programmable by means of standard digital interface (DALI) and controllable via DALI protocol
- Integrates several control options (DynaDimmer, LineSwitch, AmpDim, Constant Light Output, Adjustable Light Output)
- \cdot Longest lifetime for electronic drivers: 80,000 hours with minimum 90% survival at Tc = 80 $^{\circ}\text{C}$
- Xtreme lightning protection 10 kV/5 kA
- \cdot Accurate lamp power stabilisation of 95-97% over wide mains-voltage range of 180-300 V

DynaVision Programmable Xtreme for CPO

Application

- · Road lighting
- · Residential lighting
- City beautification


Versions








Dimensional drawing





Operating and Electrical	
Input frequency	50 to 60 Hz
Input Voltage	208-240-277 V
Line Frequency	50 to 60 Hz

Product	D1	C1	A1	A2	B1	B2
HID-DV PROG Xt 140 CPO	5.0 mm	65.0 mm	150.0 mm	135.9 mm	65.0 mm	46.8 mm
C1 208-277V						
HID-DV PROG Xt 90 CPO	5.0 mm	65.0 mm	150.0 mm	135.9 mm	65.0 mm	46.8 mm
C1 208-277V						

Product	D1	C1	A1	A2	B1	B2
HID-DV PROG Xt 140 CPO	4.5 mm	40.0 mm	150.0 mm	133.6 mm	90.0 mm	70.0 mm
Q 208-277V						
HID-DV PROG Xt 45 CPO	4.5 mm	40.0 mm	150.0 mm	133.6 mm	90.0 mm	70.0 mm
Q 208-277V						
HID-DV PROG Xt 60 CPO	4.5 mm	40.0 mm	150.0 mm	133.6 mm	90.0 mm	70.0 mm
Q 208-277V						
HID-DV PROG Xt 90 CPO	4.5 mm	40.0 mm	150.0 mm	133.6 mm	90.0 mm	70.0 mm
Q 208-277V						

Operating and Electrical

DynaVision Programmable Xtreme for CPO

		Number of products on MCB (16 A
Order Code	Full Product Name	type B) (nom.)
20455800	HID-DV PROG Xt 90 CPO C1 208-277V	5
20457200	HID-DV PROG Xt140 CPO C1 208-277V	5
24149200	HID-DV PROG Xt 60 CPO Q 208-277V	11

		Number of products on MCB (16 A
Order Code	Full Product Name	type B) (nom.)
24153900	HID-DV PROG Xt 140 CPO L1 208-277V	5
66914200	HID-DV PROG Xt 45 CPO Q 208-277V	11
24151500	HID-DV PROG Xt 90 CPO Q 208-277V	5

Mechanical and Housing

Order Code	Full Product Name	Housing
20455800	HID-DV PROG Xt 90 CPO C1 208-277V	C1
20457200	HID-DV PROG Xt140 CPO C1 208-277V	C1
24149200	HID-DV PROG Xt 60 CPO Q 208-277V	Q

Order Code	Full Product Name	Housing
24153900	HID-DV PROG Xt 140 CPO L1 208-277V	Q
66914200	HID-DV PROG Xt 45 CPO Q 208-277V	Q
24151500	HID-DV PROG Xt 90 CPO Q 208-277V	Q



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.