

# Energy savings, extra low mercury

## **Energy Advantage T8**

Philips Energy Advantage T8 lamps offer high energy savings without sacrificing performance.

#### **Benefits**

- · Operates on any Instant Start and Programmed Start Ballast‡
- · Reduce maintenance costs by extending the relamping cycle
- Reduced impact on the environment without sacrificing performance
- ‡ Starting voltage should be equal to or greater than 550V. These lamps are not recommended for use where the temperature in fixture is below 70°F. Striations may occur where air movement is present in fixture. For best operation, use ballast with anti-striation circuitry.

#### **Features**

- Save 7 watts and nearly \$26 in energy costs over the life of the lamp when comparing the Energy Advantage T8 25W XEW to a standard T8 32W lamp\*\*
- · Available in multiple wattages: 25W, 28W and 30W
- · Available in multiple color temperatures: 3000K, 3500K, 4100K, 5000K
- $\cdot$  \*\* Based on wattage savings (7W) x rated average life (38,000 hours) x kWh rate (\$ .10).

#### **Application**

 $\cdot$  Ideal for applications requiring maximum energy savings.

#### **Warnings and Safety**

- In order to ensure the integrity of the coating, it is strongly recommended to replace Secura lamps before or at the moment the specified lamp life (50% failures @ 3 hrs switching cycle) is reached.
- · Lamp contains mercury.
- · Manage in Accord with Disposal Laws.
- · See: www.lamprecycle.org or 1-800-555-0050


# **Energy Advantage T8**

## Versions



G13, T8

## Dimensional drawing



Product
F32T8/ADV830/EW/ALTO 28W 30PK
F32T8/ADV835/EW/ALTO 28W 30PK
F32T8/ADV841/EW/ALTO 28W 30PK
F32T8/ADV850/EW/ALTO 28W 30PK
F32T8/ADV835/XEW/ALTO 25W 30PK
F32T8/ADV841/XEW/ALTO 25W 30PK
F32T8/ADV850/XEW/ALTO 25W 30PK

Approval and application	
Energy Saving Product	Energy Saving
Mercury (Hg) Content (Nom)	1.7 mg
General information	
Cap-Base	G13
Life 12-Hr Instant Start [Hrs]	38000 h
Life 12-Hr Programstart [Hrs]	44000 h
Life 3-Hr Instant Start [Hrs]	32000 h
Life 3-Hr Program Start [Hrs]	38000 h
Mechanical and housing	
Bulb Shape	T8

## Approval and application

Order Code	Full Product Name	Picogram Per Lumen Hour
281014	F32T8/ADV830/EW/ALTO 28W 30PK	27 pg/lm.h
281022	F32T8/ADV835/EW/ALTO 28W 30PK	27 pg/lm.h
281030	F32T8/ADV841/EW/ALTO 28W 30PK	27 pg/lm.h
281055	F32T8/ADV850/EW/ALTO 28W 30PK	27 pg/lm.h
282095	F32T8/ADV835/XEW/ALTO 25W 30PK	29 pg/lm.h
280784	F32T8/ADV841/XEW/ALTO 25W 30PK	29 pg/lm.h
280792	F32T8/ADV850/XEW/ALTO 25W 30PK	30 pg/lm.h

## Operating and electrical

Order Code	Full Product Name	Power (Nom)
281014	F32T8/ADV830/EW/ALTO 28W 30PK	28 W
281022	F32T8/ADV835/EW/ALTO 28W 30PK	28 W
281030	F32T8/ADV841/EW/ALTO 28W 30PK	28 W
281055	F32T8/ADV850/EW/ALTO 28W 30PK	28 W

Order Code	Full Product Name	Power (Nom)
282095	F32T8/ADV835/XEW/ALTO 25W 30PK	25 W
280784	F32T8/ADV841/XEW/ALTO 25W 30PK	25 W
280792	F32T8/ADV850/XEW/ALTO 25W 30PK	25 W

## Light technical (1/2)

# **Energy Advantage T8**

Order Code 281014	Full Product Name F32T8/ ADV830/EW/ ALTO 28W 30PK	Color Code Advantage 830	Color Designation Advantage 830	Correlated Color Temperature (Nom) 3000 K	Color Rendering Index (Nom) 85
281022	F32T8/ ADV835/EW/ ALTO 28W 30PK	Advantage 835	Advantage 835	3500 K	85
281030	F32T8/ ADV841/EW/ ALTO 28W 30PK	Advantage 841	Advantage 841	4100 K	82
281055	F32T8/ ADV850/EW/	Advantage 850	Advantage 850	5000 K	82

Order	Full Product		Color	Correlated Color	Color Rendering Index
				Temperature	
Code	Name	Color Code	Designation	(Nom)	(Nom)
	ALTO 28W				
	30PK				
282095	F32T8/	Advantage	Advantage	3500 K	85
	ADV835/XEW/	835	835		
	ALTO 25W				
	30PK				
280784	F32T8/	Advantage	Advantage	4100 K	85
	ADV841/XEW/	841	841		
	ALTO 25W				
	30PK				
280792	F32T8/	Advantage	Advantage	5000 K	82
	ADV850/XEW/	850	850		
	ALTO 25W				
	30PK				

#### Light technical (2/2)

		Design Mean	Luminous Flux
Order Code	Full Product Name	Lumens	(Nom)
281014	F32T8/ADV830/EW/ALTO 28W	2645 lm	2725 lm
	30PK		
281022	F32T8/ADV835/EW/ALTO 28W	2645 lm	2725 lm
	30PK		
281030	F32T8/ADV841/EW/ALTO 28W	2645 lm	2725 lm
	30PK		
281055	F32T8/ADV850/EW/ALTO 28W	2595 lm	2675 lm
	30PK		

		Design Mean	Luminous Flux
Order Code	Full Product Name	Lumens	(Nom)
282095	F32T8/ADV835/XEW/ALTO 25W 30PK	2425 lm	2500 lm
280784	F32T8/ADV841/XEW/ALTO 25W 30PK	2425 lm	2500 lm
280792	F32T8/ADV850/XEW/ALTO 25W 30PK	2330 lm	2400 lm

