



The new classic light bulb

Halogen Classic A-shape

Philips Halogen Classic light bulbs offer the classical shapes you are used to. This new 'classic' gives high-quality light, is dimmable and starts immediately.

Benefits

- · Identical look and feel to standard lamp, with bright, sparkling halogen light
- Fully dimmable, from 0 to 100%, to meet different brightness requirements
- · Double the lifetime of a standard bulb and immediate light when switching on

Features


- Superior quality of light with excellent colour rendering (R_a=100)
- · Mains-voltage lamp, no transformer needed
- · Universal burning position
- Instant start

Application

 Accent and general lighting applications in homes, offices, shops, hotels and restaurants. Replacement for traditional bulb in classical luminaires

Halogen Classic A-shape

Dimensional drawing



Product	D (max)	C (max)
EcoClassic 105W B22 240V A55 FR 1CT/10	56 mm	95.5 mm
EcoClassic 140W B22 240V A55 FR 1CT/10	56 mm	95.5 mm

General Information Cap-Base B22 Rated Lifetime (Hours) 2,000 hour(s) Switching Cycle 8,000 Nominal lifetime 2,000 hour(s) Operating Position UNIVERSAL Light Technical Correlated Color Temperature (Nom) 2800 K Color rendering index (CRI) 100 Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted Bulb Shape A55		
Rated Lifetime (Hours) 2,000 hour(s) Switching Cycle 8,000 Nominal lifetime 2,000 hour(s) Operating Position UNIVERSAL Light Technical Correlated Color Temperature (Nom) 2800 K Color rendering index (CRI) 100 Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	General Information	
Switching Cycle 8,000 Nominal lifetime 2,000 hour(s) Operating Position UNIVERSAL Light Technical Correlated Color Temperature (Nom) 2800 K Color rendering index (CRI) 100 Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Cap-Base	B22
Nominal lifetime 2,000 hour(s) Operating Position UNIVERSAL Light Technical Correlated Color Temperature (Nom) 2800 K Color rendering index (CRI) 100 Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Rated Lifetime (Hours)	2,000 hour(s)
Operating Position Light Technical Correlated Color Temperature (Nom) 2800 K Color rendering index (CRI) 100 Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Switching Cycle	8,000
Light Technical Correlated Color Temperature (Nom) 2800 K Color rendering index (CRI) 100 Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Nominal lifetime	2,000 hour(s)
Correlated Color Temperature (Nom) 2800 K Color rendering index (CRI) 100 Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Operating Position	UNIVERSAL
Correlated Color Temperature (Nom) 2800 K Color rendering index (CRI) 100 Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted		
Color rendering index (CRI) Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Light Technical	
Operating and Electrical Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Correlated Color Temperature (Nom)	2800 K
Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Color rendering index (CRI)	100
Warm-up time to 60% light instant full light s Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted		
Voltage (Nom) 240 V Starting Time (Nom) 0.0 s Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Operating and Electrical	
Starting Time (Nom) Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Warm-up time to 60% light	instant full light s
Controls and Dimming Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Voltage (Nom)	240 V
Dimmable Yes Mechanical and Housing Bulb Finish Frosted	Starting Time (Nom)	0.0 s
Dimmable Yes Mechanical and Housing Bulb Finish Frosted		
Mechanical and Housing Bulb Finish Frosted	Controls and Dimming	
Bulb Finish Frosted	Dimmable	Yes
Bulb Finish Frosted		
	Mechanical and Housing	
Bulb Shape A55	Bulb Finish	Frosted
	Bulb Shape	A55

Light Technical

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)	Luminous Flux
925702745503	EcoClassic 105W B22 240V A55 FR 1CT/10	18.9 lm/W	1,980 lm
925702845503	EcoClassic 140W B22 240V A55 FR 1CT/10	20.3 lm/W	2,840 lm

Operating and Electrical

		Lamp Current	Power
Order Code	Full Product Name	(Nom)	Consumption
925702745503	EcoClassic 105W B22 240V A55	0.44 A	105 W
	FR 1CT/10		
	FR ICI/IO		

		Lamp Current	Power
Order Code	Full Product Name	(Nom)	Consumption
925702845503	EcoClassic 140W B22 240V A55	0.58 A	140 W
	FR 1CT/10		

Halogen Classic A-shape



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.