



Product Description

MASTER TL-D Secura

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Benefits

- Special protective coating in the lamp-, prevents products from contamination in case of accidental lamp breakage
- Easy identification in audit situations by blue ring at one end
- Special fluorescent coating gives good colour rendering
- Relatively high efficacy, both initially and during lamp lifetime, with high lumen maintenance
- Protects products from discolouring and loss of taste by 90% lower UV emission
- Compliant with HACCP regulations and supports HACCP certification

Features

- Protective coating around the entire lamp
- Blue ring around one end
- Direct retrofit for all Standard and Super /80 TL-D lamps operating on conventional or HF gear
- Highly efficient 3-band fluorescent coating in combination with New Generation pre-coating technology
- Available in various colour designations
- Low mercury dose
- Recyclable at end-of-life, including the protective lamp coating
- End-cap has green bottom plate to identify lamp as recyclable

Application

- For use where contamination resulting from lamp breakage must be prevented, e.g. in food preparation, health care, pharmaceuticals, cleanrooms etc.
- Suitable for use in environments with increased risk of breakage, e.g. sports halls
- Suitable for use in environments where UV emission should be reduced (museums, libraries, archives, food industry, fashion shops, etc.)

MASTER TL-D Secura


Warnings and Safety

- Not suitable for closed luminaires (as indicated by two blue rings)
- Recommended use in combination with self-stopping lamp control system
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- It's strongly recommended to replace Secura lamps before or at the moment the specified lamp life (50% failures @ 3 hrs switching cycle) is reached.

Versions



Dimensional drawing



Product
MASTER TL-D Secura 18W/840 SLV/25
MASTER TL-D Secura 36W/840 SLV/25

MASTER TL-D Secura

Approval and Application

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	2.0 mg

Controls and Dimming

Dimmable	yes
----------	-----

General Information

Cap-Base	G13
Life To 50% Failures Preheat (Nom)	20000 h
Life To 10% Failures (Nom)	12000 h
Life To 50% Failures (Nom)	15000 h
LSF 12000 h Rated	89 %
LSF 16000 h Rated	33 %
LSF 2000 h Rated	99 %
LSF 20000 h Rated	2 %
LSF 4000 h Rated	99 %
LSF 6000 h Rated	99 %
LSF 8000 h Rated	99 %

Light Technical

Colour Code	840
Colour Designation	Cool White (CW)
Correlated Colour Temperature (Nom)	4000 K
Colour Rendering Index (Nom)	85
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 2000 h Rated	96 %
LLMF 20000 h Rated	90 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %

Mechanical and Housing

Bulb Shape	T8
------------	----

Temperature

Design Temperature (Nom)	25 °C
--------------------------	-------

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
64010940	MASTER TL-D Secura 18W/840 1SL/25	22 kWh
64014740	MASTER TL-D Secura 36W/840 1SL/25	42 kWh

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
64010940	MASTER TL-D Secura 18W/840 1SL/25	0.360 A	18 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
64014740	MASTER TL-D Secura 36W/840 1SL/25	0.440 A	36.0 W

Light Technical

Order Code	Full Product Name	Luminous Efficacy (rated) (Nom)	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
64010940	MASTER TL-D Secura 18W/840 1SL/25	72 lm/W	1300 lm	1300 lm

MASTER TL-D Secura

Order Code	Full Product Name	Luminous	Luminous Flux (Nom)	Luminous Flux (Rated) (Nom)
		Efficacy (rated) (Nom)		
64014740	MASTER TL-D Secura 36W/840 1SL/25	89 lm/W	3200 lm	3200 lm

