



# Coreline tempo Large - For every project where light really matters

## Coreline tempo large

CoreLine tempo large is a highly efficient range of floodlights designed for 1:1 retrofit replacement of conventional technology, while retaining the same electrical installation and poles. A limited range of options makes it easy to find the best lux-for-lux replacement. The easy-to-install CoreLine tempo large offers lumen packages for many different application areas as well as a choice of high-performance asymmetrical and symmetrical optics. U-shaped universal mounting bracket and external quick 3-poles IP68 connector.

### Benefits

- Fast payback: energy savings of 65%
- Low maintenance thanks to the long lifetime of the luminaire: simple to install and connect
- Robust, high-quality finish
- Equipped with Service tag, a QR-based identification system that makes each luminaire uniquely identifiable and provides maintenance, installation and spare part information

# Coreline tempo large

## Features

- Highly efficient: up to 130 lm/W
- Designed for 1:1 retrofit replacement of conventional technology up to 400 W HPI-T
- System flux: 16 000, 21000 and 26000 lm
- Long lifetime of 75Khrs L80 at Tq +25 °C
- High-performance asymmetrical and symmetrical optics
- U-shaped universal mounting bracket and external quick 3-pole IP68 connector
- High surge protection : 6 kV/8kV
- Robust design IP66-IP68
- Extension of the options for projects : Dali control, 3000K CCT, special coatings...

## Application

- Areas and recreational sports facilities
- Building facades
- Billboards
- Landscape features
- Security and amenity lighting

## Specifications

Type	BVP130
Light source	Integral LED-module
Power	Up to 217 W (+/- 11 %)
Luminous flux	8000, 12,000, 16,000, 21,000, 26,000 lm
Luminaire efficacy	Up to 133 lm/W
Correlated Color	4000 K
Temperature	
Color Rendering Index	>70
Lumen maintenance at median useful life* 75000 h	min L80
Control gear failure rate at median useful life 75000 h	7.5%
Performance Ambient Temperature Tq	+25 °C
Operating temperature range	-30 to 35 °C
Driver	Built-in (self-ballasted LED-module)
Mains voltage	Xitanium Xtreme LITE programmable
Inrush current	53 A/160 µsec
Dimming	No
Controls system input	No
Options	CLO Module Temperature Protection (NTC)

Optic	Symmetrical Asymmetrical (I max 52°)
Optical element	Polycarbonate lens
Optical cover	Clear tempered glass, flat
Material	Housing: die-cast aluminum Lenses: metachrylate
Color	RAL9007 matt
Connection	External IP68 quick connector (3 pole)
Maintenance	No internal cleaning required
Installation	U-shaped mounting bracket with foot-print suitable for 3-point fixation by means of M20 bolts Standing-up or hanging-down mounting U-bracket stirrup with standard bolts and nuts Protractor scale with intervals of 5° Mains M20 cable gland that accept cable diameters from 10 to 14 mm with external Quick 3 poles IP68 connector No need to open the luminaire for electrical connection
Operating temperature	-40°C < Ta < 35°C
Projected area at 90°	0.15 m²
Max adjustment from the horizontal	-170 to +170°
Max vertical aiming	-90 to +90°
Cable gland	M 20
Remarks	ENEC, CE, RoHS Surge protection: 6 KV

# Coreline tempo large

## Versions



Coreline tempo large BVP130  
flood-lighting luminaire

## Product details




Coreline\_tempo\_large-BVP130-  
DP01.tif



Coreline\_tempo\_large-BVP130-  
DP02.tif



Coreline\_tempo\_large-BVP130-  
DP03.tif



Coreline\_tempo\_large-BVP130-  
DP04.tif



Coreline\_tempo\_large-BVP130-  
DP05.tif



Coreline\_tempo\_large-BVP130-  
DP06.tif

# Coreline tempo large

## Product details



Coreline\_Tempo\_Large-BVP125-DPP.TIF

### Approval and Application

Mech. impact protection code	IK08
Surge Protection (Common/Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode

### Controls and Dimming

Dimmable	No
----------	----

### General Information

CE mark	CE mark
Light source color	740 neutral white
Optical cover/lens type	Flat glass
Driver included	Yes
Flammability mark	For mounting on normally flammable surfaces
Light source replaceable	Yes
Lamp version	4S
Number of gear units	1 unit
Product Family Code	BVP130
UL mark	-

### Initial Performance (IEC Compliant)

Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>70

### Light Technical

Standard tilt angle side entry	0°
Standard tilt angle posttop	0°
Upward light output ratio	0

### Mechanical and Housing

Color	Gray
-------	------

### Operating and Electrical

Order Code	Full Product Name	Driver current
912300023660	BVP130 LED260-4S/740 OFA52	1000 mA
912300023661	BVP130 LED210-4S/740 OFA52	700 mA
912300023662	BVP130 LED160-4S/740 OFA52	780 mA
912300023663	BVP130 LED260-4S/740 S	1000 mA
912300023664	BVP130 LED210-4S/740 S	700 mA
912300023665	BVP130 LED160-4S/740 S	780 mA

## General Information (1/2)

## Coreline tempo large

Order Code	Full Product Name	Luminaire light beam spread	Lamp family code	Number of light sources	Optic type
912300023660	BVP130 LED260-4S/740 OFA52	52° x 102°	LED260	80 pcs	Optiflux asymmetrical axis angle 52°
912300023661	BVP130 LED210-4S/740 OFA52	52° x 102°	LED210	80 pcs	Optiflux asymmetrical axis angle 52°
912300023662	BVP130 LED160-4S/740 OFA52	52° x 102°	LED160	60 pcs	Optiflux asymmetrical axis angle 52°

Order Code	Full Product Name	Luminaire light beam spread	Lamp family code	Number of light sources	Optic type
912300023663	BVP130 LED260-4S/740 S	70° x 21°	LED260	80 pcs	Symmetrical
912300023664	BVP130 LED210-4S/740 S	70° x 21°	LED210	80 pcs	Symmetrical
912300023665	BVP130 LED160-4S/740 S	70° x 21°	LED160	60 pcs	Symmetrical

### General Information (2/2)

Order Code	Full Product Name	Service tag
912300023660	BVP130 LED260-4S/740 OFA52	-
912300023661	BVP130 LED210-4S/740 OFA52	-
912300023662	BVP130 LED160-4S/740 OFA52	-

Order Code	Full Product Name	Service tag
912300023663	BVP130 LED260-4S/740 S	-
912300023664	BVP130 LED210-4S/740 S	-
912300023665	BVP130 LED160-4S/740 S	Yes

### Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial luminous flux
912300023660	BVP130 LED260-4S/740 OFA52	26400 lm
912300023661	BVP130 LED210-4S/740 OFA52	21320 lm
912300023662	BVP130 LED160-4S/740 OFA52	16400 lm

Order Code	Full Product Name	Initial luminous flux
912300023663	BVP130 LED260-4S/740 S	26400 lm
912300023664	BVP130 LED210-4S/740 S	21320 lm
912300023665	BVP130 LED160-4S/740 S	16400 lm

