



# Architectural MSD – single ended night colors

## Architectural MSD

The high luminous efficacy and optimal lamp filling of the single ended Architectural MSD lamps create high beam intensity and excellent color rendering. While the compact arc of the lamp allows efficient beam control and high intensity. Ideal to illuminate architecture of all types at night.

### Benefits

- High lumen output
- Low cost of ownership
- Excellent colors

### Features

- High luminous efficacy
- Long life
- Optimal lamp filling

### Application

- Display lighting
- Architectural lighting
- Studio and disco lighting
- Fibre-optic lighting

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

# Architectural MSD

## Versions




MSD 575 HR




MSD 1200

## Dimensional drawing



### Product

MSD 575 HR 1CT/8



### Product

MSD 1200.1CT/3

### Controls and Dimming

Dimmable No

### General Information

Cap-Base G22  
Life To 50% Failures (Nom) 2000 h  
Main Application Studio/Disco  
Operating Position Universal

### Light Technical

Color Code -  
Correlated Color Temperature (Nom) 6000 K

# Architectural MSD

## Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
245472	MSD 575 HR 1CT/8	6.95 A	575 W

Order Code	Full Product Name	Lamp Current (Nom)	Power (Rated) (Nom)
245589	MSD 1200.1CT/3	13.8 A	1200 W

## General Information

Order Code	Full Product Name	System Description
245472	MSD 575 HR 1CT/8	Hot Restrike

Order Code	Full Product Name	System Description
245589	MSD 1200.1CT/3	na

## Light Technical

Order Code	Full Product Name	Color Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
245472	MSD 575 HR 1CT/8	75	40000 lm	46000 lm

Order Code	Full Product Name	Color Rendering Index (Nom)	Luminous Flux (Min)	Luminous Flux (Nom)
245589	MSD 1200.1CT/3	80	-	92000 lm

