



# TUV PL-S - Compact solution for residential applications

## TUV PL-S

TUV PL-S lamps are compact UVC (germicidal) lamps used in residential water and air disinfection units. The compact size of the lamp allows for a small system design and design flexibility. TUV PL-S lamps offer constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Thanks to the single-ended lamp base, lamp replacement is easy.

### Benefits

- Security of effective disinfection over the useful lifetime of the lamp
- High system efficacy because it is not required to over-design the purification system to maintain effectiveness of disinfection
- Good environmental choice because of lowest amount of mercury

### Features

- Short-wave UV radiation with a peak at 253.7 nm (UVC) for disinfection purposes
- Protective inside coating ensures constant UV output over the complete lifetime of the lamp
- Lamp glass filters out the 185 nm ozone-forming radiation
- 2-Pin PL-S lamp base contains a special starter for almost instant starting on electromagnetic drivers
- 4-Pin PL-S lamps are designed for use on electronic drivers
- Warning sign on lamp indicates that the lamp radiates UVC

# TUV PL-S

## Application

- Deactivation of bacteria, viruses and other micro-organisms
- Residential drinking water units
- Pond water units
- Air treatment units
- Stand-alone purifiers

## Versions




TUV PL-S G23




TUV PL-S 2G7

## Dimensional drawing



Product	D1 (max)	D (max)	A (max)	B (max)	C (max)
TUV PL-S 5W/2P 1CT/6X10BOX	13 mm	28 mm	67 mm	83 mm	105 mm
TUV PL-S 9W/2P 1CT/6X10BOX	13 mm	28 mm	129 mm	144.5 mm	167 mm



Product	D1 (max)	D (max)	A (max)	B (max)	C (max)
TUV PL-S 9W/4P 1CT/ 6X10BOX	13 mm	28 mm	127.2 mm	144.5 mm	151.1 mm

# TUV PL-S

## Approval and Application

Mercury (Hg) Content (Nom) 3.0 mg

## General Information

Useful Life (Nom) 9000 h

Main Application Disinfection

## Light Technical

Color Code TUV

Color Designation -

Lumen Depreciation At Useful Lifetime 20 %

## Mechanical and Housing

Bulb Shape 2xT12

## Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Voltage (Nom)	Power (Rated) (Nom)
381863	TUV PL-S 5W	0.18 A	34 V	5.5 W
325126	PL-S 9W/TUV 60PK	0.17 A	60 V	9 W

Order Code	Full Product Name	Lamp Current (Nom)	Voltage (Nom)	Power (Rated) (Nom)
285668	TUV PL-S 9W/4P 1CT/ 6X10BOX	0.17 A	60 V	8.6 W

## General Information

Order Code	Full Product Name	Cap-Base
381863	TUV PL-S 5W	G23
325126	PL-S 9W/TUV 60PK	G23

Order Code	Full Product Name	Cap-Base
285668	TUV PL-S 9W/4P 1CT/6X10BOX	2G7

## UV

Order Code	Full Product Name	UV-C Radiation
381863	TUV PL-S 5W	1.1 W
325126	PL-S 9W/TUV 60PK	2.3 W

Order Code	Full Product Name	UV-C Radiation
285668	TUV PL-S 9W/4P 1CT/6X10BOX	2.3 W

