



# Flexible and tunable white

## Flex Cove G4

A sustainable and flexible offering with excellent optical performance

### Benefits

- Energy efficient
- Great diversity
- Dimming compatibility

### Features

- System efficacy up to 110 lm/W
- 4 lumen options, 4 CCTs
- Tunable white 1,000~4,000 k and 2,700~6,500 K

### Application

- Hotel
- Retail
- Restaurant

## Flex Cove G4

### Application conditions

Ambient temperature range	-20 to +35 °C
Maximum dimming level	Not applicable

### Approval and application

Mech. impact protection code	IK00
Ingress protection code	IP20

### Controls and dimming

Dimmable	No
----------	----

### Operating and electrical

Input Voltage	24 DC V
---------------	---------

### General information

Beam angle of light source	120 °
CE mark	-
Protection class IEC	Safety class III (III)
Optical cover/lens type	No
Driver included	No
ENEC mark	-
Flammability mark	NO
Glow-wire test	NO
Light source replaceable	No
Number of gear units	-
Optic type	Symmetrical

### Initial performance (IEC compliant)

Initial chromaticity	0.463;0.42; SDCM 3
Init. Corr. Colour Temperature	2700 K
Init. Colour rendering index	90
Initial LED luminaire efficacy	80 lm/W
Luminous flux tolerance	+/-10%

### Mechanical and housing

Colour	White
--------	-------

### Initial performance (IEC compliant)

Order Code	Full Product Name	Initial luminous flux	Initial input power
911401759722	LS170S LED8 927 IP20 L5000	800 lm	41 W
911401759742	LS170S LED16 927 IP20 L5000	1600 lm	85 W

