



# Philips Villa LED gen2: iconic Iberian four- sided luminaire

## Villa LED gen2

Philips Villa LED gen2 is designed to offer the perfect balance between heritage preservation and performance. Designed with the specific proportions and shape of the traditional four-sided luminaires originally used in Madrid in the 19th century, Villa LED gen2 is now widely used for street lighting in historical environments and traditional towns and villages across the Iberian Peninsula. Thanks to the Philips LEDGINE-O engine, and the wide range of application-tailored optics, Villa LED gen2 delivers the right amount of light precisely where it is needed, enabling further energy savings. This urban lamp can even be equipped with our dedicated light recipe that preserves dark skies. Villa LED gen2 is also future ready with a choice of one or two Philips System Ready (SR) sockets that enable the luminaire to be paired with both standalone and advanced control and lighting software applications such as Interact from Signify. In addition, every Villa LED gen2 luminaire is uniquely identifiable, thanks to the Signify Service tag app. By simply scanning a QR code, placed inside the door of the mast or directly on the luminaire, you can instantly access the configuration of the luminaire. This makes maintenance and programming operations faster and easier, and enables you to create a digital library of lighting assets and spare parts.

### Benefits

- Iconic luminaire for contemporary and historical environments
- Covers a wide range of urban lighting applications for roads and streets with different geometries
- Future-proof thanks to SR socket compatible with all Philips' standard and advanced lighting controls
- Service tag for easy installation and maintenance

## Villa LED gen2

### Features

- Historical shape
- Large choice of different beams, internal louvers to minimize glare
- Variety of mounting options: luminaire can be combined with different columns, brackets and multiple-arm brackets

### Application

- Main urban roads and streets, side and residential roads and streets
- City centers and historical areas
- Cycle and pedestrian paths, squares, parks and playgrounds

### Versions






BDP768 40led without flush  
transition part



BDP768 BDP651 without spigot  
RET

### Dimensional drawing



# Villa LED gen2

General Information	
CE mark	Yes
Driver included	Yes
Flammability mark	-
Lamp family code	LED50
Light source replaceable	Yes
Number of gear units	1 unit
Light Technical	
Luminaire light beam spread	30° - 5° x 153°
Light source color	830 warm white
Correlated Color Temperature (Nom)	3000 K
Color rendering index (CRI)	≥80
Optic type outdoor	Distribution medium 50
Standard tilt angle side entry	-
Standard tilt angle posttop	-
Upward light output ratio	0.01
Operating and Electrical	
Power Consumption	38 W
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Color	Black
Approval and Application	
Mech. impact protection code	IK09
Ingress protection code	IP66
Surge Protection (Common/ Differential)	Luminaire surge protection level until 6 kV differential mode and 8 kV common mode

## General Information

Order Code	Full Product Name	Product family code
912300024527	BDP768 LED50/830 II DM50 MK-BK FG BALL 6	BDP768
912300024528	BDP768 LED50/830 II DM50 MK-BK FG BALL 3	BDP768
912300024430	BSP768 LW LED50/830 II DM50 MK-BK FG BAL	BSP768
912300060153	BSP768 LED50/830 II DM50 MK-BK GF BALL 3	BSP768
912300060154	BSP768 LED50/830 II DM50 MK-WH FG BALL 3	BSP768
912300060155	BSP768 LED50/830 II DM50 MK-WH GF BALL 3	BSP768

## Light Technical

Order Code	Full Product Name	Optical cover	
		type	Luminous Flux
912300024527	BDP768 LED50/830 II DM50 MK-BK FG BALL 6	Flat glass	3,450 lm
912300024528	BDP768 LED50/830 II DM50 MK-BK FG BALL 3	Flat glass	3,450 lm
912300024430	BSP768 LW LED50/830 II DM50 MK- BK FG BAL	Flat glass	3,450 lm

Order Code	Full Product Name	Optical cover	
		type	Luminous Flux
912300060153	BSP768 LED50/830 II DM50 MK-BK GF BALL 3	Glass frosted	3,100 lm
912300060154	BSP768 LED50/830 II DM50 MK-WH FG BALL 3	Flat glass	3,700 lm
912300060155	BSP768 LED50/830 II DM50 MK-WH GF BALL 3	Glass frosted	3,250 lm

