



The new generation of energy-saving LED PLC 4P tube lighting

CorePro LED PLC 4P

The CorePro LED PLC 4P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplampping in general lighting applications: it meets basic lighting requirements, offers significant energy savings, and is environmentally friendly.

Benefits

- Reduced operational cost thanks to lower energy consumption
- Lower maintenance cost thanks to 2-3 times longer lifetime than conventional lamps
- Fastest and easiest way to upgrade existing luminaires to LED technology
- Completely safe product and installation process

Features

- Highly energy-efficient
- Easy installation
- Conventional form factor to fit into existing luminaires
- No mercury

Application

- Hospitality, retail, office, industrial and home applications



CorePro LED PLC 4P

Versions



SPPR MLEDGA 0026

Dimensional drawing



Product	D1	D2	A1	A2	A3
CorePro LED PLC 6.5W 830 4P G24q-2	24.3 mm	28.4 mm	105.8 mm	125 mm	140.6 mm
CorePro LED PLC 6.5W 840 4P G24q-2	24.3 mm	28.4 mm	105.8 mm	125 mm	140.6 mm

Product	D1	D2	A1	A2	A3
CorePro LED PLC 9W 830 4P G24q-3	24.3 mm	28.4 mm	128.8 mm	148 mm	163.6 mm
CorePro LED PLC 9W 840 4P G24q-3	24.3 mm	28.4 mm	128.8 mm	148 mm	163.6 mm

CorePro LED PLC 4P

General Information	
Switching Cycle	50,000
Nominal lifetime	30,000 hour(s)
Light Technical	
Beam Angle (Nom)	120 degree(s)
Color rendering index (CRI)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	30000-80000 Hz
Line Frequency	30000-80000 Hz
Starting Time (Nom)	0.5 s
Temperature	
Ambient temperature range	-20 °C to 35 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	PL-C

General Information

Order Code	Full Product Name	Cap-Base
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	G24q-2
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	G24q-2
54115900	CorePro LED PLC 9W 830 4P G24q-3	G24q-3
54117300	CorePro LED PLC 9W 840 4P G24q-3	G24q-3

Light Technical

Order Code	Full Product Name	Correlated Color	Color	
		Temperature (Nom)	Code	Luminous Flux
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	3000 K	830	650 lm
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	4000 K	840	700 lm

Order Code	Full Product Name	Correlated Color	Color	
		Temperature (Nom)	Code	Luminous Flux
54115900	CorePro LED PLC 9W 830 4P G24q-3	3000 K	830	950 lm
54117300	CorePro LED PLC 9W 840 4P G24q-3	4000 K	840	1,000 lm

Operating and Electrical

Order Code	Full Product Name	Power Consumption
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	6.5 W
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	6.5 W

Order Code	Full Product Name	Power Consumption
54115900	CorePro LED PLC 9W 830 4P G24q-3	9 W
54117300	CorePro LED PLC 9W 840 4P G24q-3	9 W

Temperature

Order Code	Full Product Name	T-Case Maximum (Nom)
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	66 °C
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	66 °C

Order Code	Full Product Name	T-Case Maximum (Nom)
54115900	CorePro LED PLC 9W 830 4P G24q-3	76 °C
54117300	CorePro LED PLC 9W 840 4P G24q-3	76 °C

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/1000 h
54119700	CorePro LED PLC 6.5W 830 4P G24q-2	7 kWh
54121000	CorePro LED PLC 6.5W 840 4P G24q-2	7 kWh
54115900	CorePro LED PLC 9W 830 4P G24q-3	9 kWh
54117300	CorePro LED PLC 9W 840 4P G24q-3	9 kWh

CorePro LED PLC 4P

