

Breathe healthy air (DESIGNED FOR PROFESSIONAL ONLY)

UV-C disinfection upper air wall mounted

As part of the Philips UV-C disinfection upper air device series, Philips UV-C disinfection upper air wall mounted is designed to be installed on walls for the disinfection of air in a wide range of applications. Optimized for low ceiling heights, the UV-C rays are distributed at device level and above. The beam of UV-C rays is controlled by specific reflectors and the louvre design. This allows for the disinfection of the air in a space, while ensuring that day-to-day business activities can continue underneath the area where the device is active.

Benefits

- Our Philips UV-C disinfection upper air wall mount luminaires inactivated 99.99% of SARS-COV-2, the virus responsible for the COVID-19 disease, in the air of a room within 10 minutes. At 20 minutes, the virus was below detectable levels. [1]
- Swift disinfection effect, with 83.6% reduction of SARS-CoV-2, the virus that causes the COVID-19 disease, achieved in a room within 2 minutes. [1]
- Allows quiet disinfection of air while business activity continues underneath the device's level
- Uses Philips UV-C lamps and drivers
- Environmentally friendly - no ozone emissions during or after use

UV-C disinfection upper air wall mounted

Features

- Philips T5 TUV 25W lamp included
- Shortwave UV radiation peak at 253.7 nm (UV-C)
- Louvres and reflector control the distribution of UV-C at the device level and above, where people are not usually present
- Wall mounted installation
- Complies with IEC 62471 standard for photobiological safety

Application

- Office
- Retail
- Food outlets
- Hospitality
- Schools
- Banking
- Washrooms

Warnings and Safety

- **DANGER:** Risk Group 3 UV product. Like any disinfection system, UV-C lamps and devices must be installed and used in the correct way. Direct exposure to UV-C can be dangerous and result in a sunburn-like reaction to the skin and serious damage to the cornea. As UV-C is invisible to the eye, the UV-C upper air device must be installed together with adequate safeguards to ensure that the UV-C upper air device can be operated in a safe way. The UV-C upper air device are only to be used as components in a system that consists of adequate safety safeguards such as, but not limited to, those indicated in the mounting instructions and/or user manuals. Direct exposure to UV-C is dangerous. Philips UV-C luminaires systems must only be sold through qualified partners and installed by professionals according to our stringent safety and legal requirements. Our UV-C products are not meant to be used in applications or activities which may cause and/or lead to death, personal injury and/or damage to the environment.
- [1] According to results obtained from a laboratory test conducted by Innovative Bioanalysis, a CAP, CLIA, AABB Certified Safety Reference Laboratory, in a room with sufficient air circulation. For more information, please refer to the test report available in the "related tools" part of this webpage

Versions




UV-C disinfection upper air Wall mounted version high output



UV-C disinfection upper air Wall mounted version

UV-C disinfection upper air wall mounted


Dimensional drawing



Product details



Access to lamp and product maintenance



Wall mounting plate and indicator light

UV-C disinfection upper air wall mounted

General Information

CE mark	Yes
ENEC mark	-
Flammability mark	-
Gear	HF-S
Glow-wire test	Temperature 650 °C, duration 30 s
Number of gear units	1 unit
Product family code	WL345W
EU RoHS compliant	Yes
Warranty period	1 years

Light Technical

Number of light sources	1
Optic type	Lamellae louver

Operating and Electrical

Cable	-
Connection	Push-in connector 3-pole
Inrush current	18 A
Inrush time	0.35 ms
Input Voltage	230 V
Number of products on MCB of 16 A type B	28
Power Factor (Fraction)	0.98

Temperature

Ambient temperature range	+10 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Housing Color	White and black
Housing Material	Aluminum
Optic material	Aluminum
Reflector material	Aluminum
Overall height	140 mm

Approval and Application

Protection class IEC	Safety class I
Mech. impact protection code	IK02
Ingress protection code	IP20

Initial Performance (IEC Compliant)

Power consumption tolerance	+/-10%
-----------------------------	--------

Application Conditions

Suitable for random switching	No
-------------------------------	----

UV

Order Code	Full Product Name	UV-C irradiance defined		UV-C radiation
		at 0.2m	at 2m	
919206000111	WL346W 1xTUV T5 25W HFS	8,060 mW/m ²	972 mW/m ²	0.53 W
919206000011	WL345W 1xTUV T5 25W HFS	4,266 mW/m ²	356 mW/m ²	0.375 W

UV-C disinfection upper air wall mounted

