



Tango G2 LED

BVP283 LED262/CW 200W 220-240V AWB

Tango G2 LED, 26200 lm, 200 W, 757 cool white, Safety class I

Tango G2 LED is a general purpose LED flood lighting luminaire for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

Product data

General Information		Connection	
Driver included	Yes	Flying leads/wires	
Lighting Technology	LED	Cable	
CE mark	CE mark	Cable 0.5 m without plug	
Light Technical		Temperature	
Luminous Flux	26,200 lm	Ambient temperature range	
Correlated Color Temperature (Nom)	5700 K	-40 to +50 °C	
Luminous Efficacy (rated) (Nom)	130 lm/W	Controls and Dimming	
Color rendering index (CRI)	>70	Dimmable	
Light source color	757 cool white	No	
Optical cover type	Polycarbonate micro lens optic	Control interface	
Operating and Electrical		-	
Input Voltage	220 to 240 V	Mechanical and Housing	
Line Frequency	50 or 60 Hz	Housing Material	
Power Consumption	200 W	Aluminum die cast	
Power Factor (Fraction)	0.9	Optical cover material	
		Polycarbonate	
		Housing Color	
		Aluminum and gray	
		Approval and Application	
		Ingress protection code	
		IP65 [Dust penetration-protected, jet-proof]	
		Mech. impact protection code	
		IK08 [5 J vandal-protected]	

Tango G2 LED

Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%
Product Data	
Order product name	BVP283 LED262/CW 200W 220-240V AWB

Full product name	BVP283 LED262/CW 200W 220-240V AWB
Full product code	911401692505
Order code	911401692505
Material Nr. (12NC)	911401692505
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing

