

# **Tango G2 LED**

## BVP283 LED430/NW 335W 220-240V SWB

Tango G2 LED, 43000 lm, 335 W, 740 neutral white, Safety class

Tango G2 LED is a general purpose LED flood lighting luminiare for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

#### **Product data**

General Information	
Driver included	Yes
Lighting Technology	LED
CE mark	CE mark
Light Technical	
Luminous Flux	43,000 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	130 lm/W
Color rendering index (CRI)	>70
Light source color	740 neutral white
Optical cover type	Polycarbonate micro lens optic
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
· · · · · · · · · · · · · · · · · · ·	

Power Consumption	335 W
Power Factor (Fraction)	0.9
Connection	Flying leads/wires
Cable	Cable 0.5 m without plug
Temperature	
Ambient temperature range	-40 to +50 °C
Controls and Dimming	
Dimmable	No
Control interface	-
Mechanical and Housing	
Housing Material	Aluminum die cast
Optical cover material	Polycarbonate


Datasheet, 2023, April 29 data subject to change

## Tango G2 LED

Aluminum and gray	
IP65 [Dust penetration-protected, jet-proof]	
IK08 [5 J vandal-protected]	
Safety class I	
Initial Performance (IEC Compliant)	
+/-10%	
+/-10%	

Product Data	
Order product name	BVP283 LED430/NW 335W 220-240V SWB
Full product name	BVP283 LED430/NW 335W 220-240V SWB
Full product code	911401698005
Order code	911401698005
Material Nr. (12NC)	911401698005
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Numerator - Packs per outer box	I

### Dimensional drawing





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.