



# UNIUrban

## BSP461 LED78 NW 110-277V TS

UNIUrban, 7800 lm, 65 W, Neutral white, Safety class I, Catenary pole 35mm with Ø 10mm hole

UNIUrban is ideal for urban lighting across pathways, parks, gardens, residential areas and shopping centre areas. Its exquisite, stylish yet classic design is not only suitable for modern cities but also for historical architecture.

### Product data

<b>General Information</b>		<b>Power Consumption</b>	
Light source replaceable	No	Power Factor (Fraction)	0.95
Driver included	Yes	Connection	Flying leads/wires
Light source engine type	LED	Cable	Cable 0.6 m without plug
Value ladder	Performance	<b>Temperature</b>	
CE mark	CE mark	Ambient temperature range	-40 to +50 °C
Flammability mark	-	<b>Controls and Dimming</b>	
<b>Light Technical</b>		Dimmable	No
Luminous Flux	7,800 lm	Control interface	-
Standard tilt angle posttop	-	Constant light output	No
Correlated Color Temperature (Nom)	4000 K	<b>Mechanical and Housing</b>	
Luminous Efficacy (rated) (Nom)	120 lm/W	Housing Material	Aluminum
Color rendering index (CRI)	≥70	Optical cover material	Tempered glass
Light source color	Neutral white	Housing Color	Grey
Optical cover type	Polycarbonate micro lens optic	Mounting device	Catenary pole 35mm with Ø 10mm hole
<b>Operating and Electrical</b>		Optical cover finish	Clear
Input Voltage	110 to 277 V	Overall height	112 mm
Line Frequency	50 to 60 Hz		

Overall diameter	482 mm
<b>Approval and Application</b>	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

<b>Product Data</b>	
Order product name	BSP461 LED78 NW 110-277V TS
Full product name	BSP461 LED78 NW 110-277V TS
Full product code	911401727672
Order code	911401727672
Material Nr. (12NC)	911401727672
Local order code	USPLED78NWTS
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

## Dimensional drawing

