



Electronic semiparallel ignitor for HID lamp circuits

SN 57

HID ignitors for semi-parallel systems

Product data


Input Voltage 220 to 240 V Line Frequency 50 to 60 Hz Input Frequency 50 to 60 Hz Wiring Connector Type Screw Temperature Ambient temperature range -20 °C to 75 °C T-Case Maximum (Max) 80 °C Mechanical and Housing Housing Akulon S223			
Line Frequency 50 to 60 Hz Input Frequency 50 to 60 Hz Wiring Connector Type Screw Temperature Ambient temperature range -20 °C to 75 °C T-Case Maximum (Max) 80 °C	Operating and Electrical		
Input Frequency 50 to 60 Hz Wiring Connector Type Screw Temperature Ambient temperature range -20 °C to 75 °C T-Case Maximum (Max) 80 °C Mechanical and Housing	Input Voltage	220 to 240 V	
Wiring Connector Type Screw Temperature Ambient temperature range T-Case Maximum (Max) Mechanical and Housing	Line Frequency	50 to 60 Hz	
Connector Type Screw Temperature Ambient temperature range -20 °C to 75 °C T-Case Maximum (Max) 80 °C Mechanical and Housing	Input Frequency	50 to 60 Hz	
Connector Type Screw Temperature Ambient temperature range -20 °C to 75 °C T-Case Maximum (Max) 80 °C Mechanical and Housing			
Temperature Ambient temperature range -20 °C to 75 °C T-Case Maximum (Max) 80 °C Mechanical and Housing	Wiring		
Ambient temperature range -20 °C to 75 °C T-Case Maximum (Max) 80 °C Mechanical and Housing	Connector Type	Screw	
Ambient temperature range -20 °C to 75 °C T-Case Maximum (Max) 80 °C Mechanical and Housing			
T-Case Maximum (Max) 80 °C Mechanical and Housing	Temperature		
Mechanical and Housing	Ambient temperature range	-20 °C to 75 °C	
	T-Case Maximum (Max)	80 °C	
Housing Akulon S223	Mechanical and Housing		
	Housing	Akulon S223	
	Housing	Akulon S223	

Approval and Application		
Approval Marks	CE marking ENEC certificate	
Product Data		
rder product name	SN 57	
ull product name	SN 57	
ull product code	697013372883300	
der code	913710010613	
aterial Nr. (12NC)	913710010613	
umerator - Quantity Per Pack	1	
AN/UPC - Product/Case	6970133728833	
umerator - Packs per outer box	48	
AN/UPC - Case	6970133728840	

Datasheet, 2023, April 15 data subject to change

Electronic semi-parallel ignitor for HID lamp circuits

Dimensional drawing



Product	C1	A1	A2	B1
SN 57	38.5 mm	85.5 mm	65.0 mm	41.5 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.