



# HF-Essential II for TL5/TL-D

## HF-E II 136 TL-D 220-240V 50/60Hz

Essentially smart and reliable. HF-Essential II is the most cost-effective solution for reliably operation of a fluorescent lamp. It is also the ideal entry-level product for electromagnetic system users who want to take advantage of the benefits provided by electronic ballasts. The cost-saving and reliable HF-Essential II is energy efficiency class A2, and its robust design meets all relevant international safety and performance standards. HF- Essential II is the ideal choice for a broad range of new construction and retrofit applications within the commercial sector, including general surface mounting and office lighting, parking garages, warehouses and other applications. The ballast is primarily designed for Indoor application. For outdoor application, the luminaire should be minimum Classland need to be sufficiently protected against water & dust. The installation should also be guard against any lightening surge or any other necessary electrical protection as deemed in such typical installation & application.

### Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Earth Leakage Current (Max)	0.5 mA
Inrush Current Width	0.37 ms
Inrush Current Peak (Max)	15 A
Number of Products on MCB (16A Type B) (Nom)	20
Wiring	
Connector Type Input Terminals	Insert


Connector Type Output Terminals	Insert
Temperature	
Ambient temperature range	-10 °C to 50 °C
T-Case Lifetime (Nom)	80 °C
T-Case Maximum (Max)	80 °C
Mechanical and Housing	
Housing	L 150x40x28
Approval and Application	
Ingress protection code	IP20 [Finger-protected]

HF-Essential II for TL5/TL-D

Energy Efficiency Index	A2
Approval Marks	CE marking CB Certificate KEMA Keur certificate RoHS Compliant
Product Data	
Order product name	HF-E II 136 TL-D 220-240V 50/60Hz
Full product name	HF-E II 136 TL-D 220-240V 50/60Hz
Full product code	871829177056500

Order code	913713041066
Material Nr. (12NC)	913713041066
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291770565
Numerator - Packs per outer box	20
EAN/UPC - Case	8718291770572

Dimensional drawing



Product	D1	C1	A1	A2	B1
HF-E II 136 TL-D 220-240V 50/60Hz	4.2 mm	28.0 mm	150.0 mm	138.0 mm	39.6 mm

