



Capsuleline

Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F

Single-ended low-voltage halogen capsule giving crisp white halogen light

Product data

General Information	
Cap base	GY6.35 [GY6.35]
Operating position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 h
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 h
Lighting Technology	Halogen
Light Technical	
Luminous Flux	850 lm
Correlated Colour Temperature	2900 K
Luminous efficacy (rated) (nom.)	17 lm/W
Colour rendering index (CRI)	100
Operating and Electrical	
Power Consumption	50.0 W
Lamp current (nom.)	4.17 A
Starting time (nom.)	0.0 s
Warm-up time to 60% light	Instant full light s
Power Factor (Fraction)	1
Voltage (nom.)	12 V
Voltage (nom.)	12 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Lamp Finish	Clear
Bulb shape	T11 [T 11 mm]
Approval and Application	
Energy consumption kWh/1,000 hours	53 kWh
Product Data	
Order product name	Caps 50W GY6.35 12V CL 2000h 1CT/10X10F
Full product name	Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F
Full EOC	871150041295950
Order code	41295950
Material no. (12 NC)	924892217108
Local order code	14567
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8711500412959
Numerator – packs per outer box	100
EAN/UPC – Case	8711500425829

Dimensional drawing



Product	D (max)	L	C (max)
Caps 50W GY6.35 12V CL 2000h 1CT/10X10F	12 mm	30 mm	44 mm

