



# Capsuleline

## Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F

Single-ended low-voltage halogen capsule giving crisp white halogen light

### Product data


General Information	
Cap base	GY6.35 [ GY6.35]
Philips code	14730
Operating position	UNIVERSAL [ Any/Universal]
Nominal lifetime (nom.)	2000 h
Switching cycle	8000X
Light Technical	
Luminous flux (nom.)	850 lm
Luminous flux (rated) (nom.)	850 lm
Correlated colour temperature (nom.)	2900 K
Luminous efficacy (rated) (nom.)	17 lm/W
Color rendering index (nom.)	100
LLMF at end of nominal lifetime (min.)	80 %
Operating and Electrical	
Power (Rated) (Nom)	50.0 W
Lamp current (nom.)	4.17 A
Starting time (nom.)	0.0 s
Warm-up time to 60% light (nom.)	instant full light
Power factor (nom.)	1
Voltage (Nom)	12 V

Controls and Dimming	
Dimmable	yes
Mechanical and Housing	
Bulb finish	Clear (CL)
Cap base information	na [ -]
Approval and Application	
Energy efficiency label (EEL)	C
Energy Consumption kWh/1000 h	53 kWh
Luminaire Design Requirements	
Bulb temperature (max.)	250 °C
Pinch temperature (max.)	350 °C
Product Data	
Full product code	871150041295950
Order product name	Capsuleline 50W GY6.35 12V CL 2000h 1CT/10X10F
EAN/UPC – product	8711500412959
Order code	41295950
Local Code	14567
Numerator – quantity per pack	1
Numerator – packs per outer box	100
Material no. (12NC)	924892217108

## Capsuleline

Net weight (piece)	0.002 kg
ILCOS Code	HSG/C/UB-50-12-GY6.35

### Dimensional drawing



CAP Fighter 14730 50W GY6.35 12V CL

Product	D (max)	L	C (max)
Capsuleline 50W GY6.35 12V CL 2000h 1CT/ 10X10F	12 mm	30 mm	44 mm

