



# **Halogen Classic P45**

## ClassicHalo 28W E14 240V P45FR 2PF/10x10

Philips Halogen Classic light bulbs offer the classical shapes you are used to. This new 'classic' gives high-quality light, is dimmable and starts immediately.

#### **Product data**


General Information	
Cap-Base	E14 [E14]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal lifetime	2,000 hour(s)
Switching Cycle	8,000
Rated Lifetime (Hours)	2,000 hour(s)
Lighting Technology	Halogen
Light Technical	
Luminous Flux	370 lm
Correlated Color Temperature (Nom)	2800 K
Luminous Efficacy (rated) (Nom)	12.4 lm/W
Color rendering index (CRI)	100
Operating and Electrical	
Power Consumption	28 W
Lamp Current (Nom)	0.12 A
Starting Time (Nom)	0.0 s
Warm-up time to 60% light	instant full light s
Power Factor (Fraction)	1
Voltage (Nom)	240 V

Voltage (Nom)	240 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	P45 [P 45mm]
Product Data	
Order product name	ClassicHalo 28W E14 240V P45FR 2PF/10x10
Full product name	ClassicHalo 28W E14 240V P45FR 2PF/10x10
Full product code	871829170041800
Order code	925715645501
Material Nr. (12NC)	925715645501
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291700418
Numerator - Packs per outer box	100
EAN/UPC - Case	8718291700432
·	· · · · · · · · · · · · · · · · · · ·

Datasheet, 2023, September 4 data subject to change

### Halogen Classic P45

#### Dimensional drawing



Product	D (max)	C (max)
ClassicHalo 28W E14 240V P45FR 2PF/10x10	46 mm	80 mm



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.