



Blue (/52) - PL-L, PL-S

PL-L 18W/52/4P 1CT/25

By emitting light almost entirely within the 400 to 500 nm bandwidth and peaking at 450 nm, Philips PL-L/PL-S color 52 lamps have no radiation from the short wave UVB. waveband. They are therefore suitable to be used in systems for applications such as Agriculture and Neonatal Jaundice Phototherapy

Warnings and Safety

- lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take them to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Photobiological safety – IEC 62471 - Risk Group 2. CAUTION - Possibly hazardous optical radiation emitted from these products.

Product data

General Information	
Cap-Base	2G11

Light Technical	
Color Code	52
Luminous Flux	330 lm
Chromaticity Coordinate X (Nom)	155
Chromaticity Coordinate Y (Nom)	75

Operating and Electrical	
Power Consumption	17.5 W
Lamp Current (Nom)	0.375 A
Voltage (Nom)	57 V
Voltage (Nom)	57 V

Mechanical and Housing	
Bulb Shape	2xT16

Approval and Application	
Mercury (Hg) Content (Nom)	4.4 mg


Product Data	
Order product name	PL-L 18W/52/4P 1CT/25
Full product name	PL-L 18W/52/4P 1CT/25
Full product code	872790080517800
Order code	927904105206
Material Nr. (12NC)	927904105206
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8727900805178
Numerator - Packs per outer box	25

Blue (/52) - PL-L, PL-S

EAN/UPC - Case

8727900805185

Dimensional drawing



Product	D1 (max)	D (max)	A (max)	B (max)	C (max)
PL-L 18W/52/4P 1CT/25	18 mm	39 mm	188.2 mm	214 mm	220.6 mm

