TL-D consumer products

G A↑G

TL-D 36W/840 1PP/10

The lamp can be operated in existing TL-D luminaire and is available in a wide range of wattages and colors.

Warnings and Safety
· A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information

Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	15,000 hour(s)

Light Technical

Color Code	840 [CCT of 4000K]
Luminous Flux	3,350 lm
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	0.38
Chromaticity Coordinate Y (Nom)	0.38
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	93 lm/W
Color rendering index (CRI)	80

Operating and Electrical

Power Consumption	36.8 W

Lamp Current (Nom)	0.440 A

Controls and Dimming

Dimmable	Yes

Mechanical and Housing

Bulb Shape	T8

Approval and Application

Energy Efficiency Class	G
Mercury (Hg) Content (Nom)	1.7 mg
Energy Consumption kWh/1000 h	37 kWh
EPREL Registration Number	423382

Product Data

Order product name	TL-D 36W/840 1PP/10
Full product name	TL-D 36W/840 1PP/10
Full product code	871150062268625

TL-D consumer products

Order code	927921084022		**Numerator – Packs per outer box**	10
Material Nr. (12NC)	927921084022		**EAN/UPC – Case**	8711500622815
Numerator – Quantity Per Pack	1			
EAN/UPC – Product/Case	8711500622686			

Dimensional drawing

| Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 36W/840 1PP/10	28 mm	1,199.4 mm	1,206.5 mm	1,204.1 mm	1,213.6 mm

Photometric data

Lifetime

Life Expectancy Diagram – TL-D 36W/840 1PP/10

Life Expectancy Diagram – TL-D 36W/840 1PP/10

TL-D consumer products

Lifetime

Lumen Maintenance Diagram – TL-D 36W/840 1PP/10

www.lighting.philips.com

2024, February 21 – data subject to change