# Lighting

**PHILIPS** 

## G A G

## MASTER TL-D Super 80

### MASTER TL-D Super 80 58W/827 1SL/25

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

#### Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**


General Information			
Cap base	G13 [Medium Bi-Pin Fluorescent]		
Flux measurement reference	Sphere		
Life to 50% failures (nom.)	15,000 h		
Light Technical			
Colour Code	827 [CCT of 2700K]		
Luminous Flux	5,240 lm		
Colour designation	Incandescent White		
Chromaticity Coordinate X (Nom)	0.463		
Chromaticity Coordinate Y (Nom)	0.42		
Correlated Colour Temperature	2700 K		
Luminous efficacy (rated) (nom.)	90 lm/W		
Colour rendering index (CRI)	82		
Operating and Electrical			
Power Consumption	59.4 W		
Lamp current (nom.)	0.670 A		

Controls and Dimming				
Dimmable	Yes			
Mechanical and Housing				
Bulb shape	T8 [26 mm (T8)]			
Approval and Application				
Energy Efficiency Class	G			
Mercury (Hg) content (nom.)	1.7 mg			
Energy consumption kWh/1,000 hours	60 kWh			
EPREL registration number	423392			
Product Data				
Order product name	MASTER TL-D Super 80 58W/827 1SL/25			
Full product name	MASTER TL-D Super 80 58W/827 1SL/25			
Full EOC	871150063210440			
Order code	63210440			
Material no. (12 NC)	927922082723			
Local order code	58827			

#### MASTER TL-D Super 80


SAP numerator – quantity per pack 1		EAN/UPC - Case	8711500632111
EAN/UPC — Product/Case	8711500632104		
Numerator – packs per outer box	25		

#### **Dimensional drawing**




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80	28 mm	1,500.0 mm	1,507.1 mm	1,504.7 mm	1,514.2 mm
58W/827 1SL/25					

#### Photometric data




Spectral Power Distribution Colour - MASTER TL-D Super 80 58W/827 1SL/25

#### Lifetime




Life Expectancy Diagram - MASTER TL-D Super 80 58W/827 1SL/25



Life Expectancy Diagram - MASTER TL-D Super 80 58W/827 1SL/25

#### **MASTER TL-D Super 80**

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 58W/827 1SL/25



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 8 - data subject to change