



MASTER TL-D Super 80



MASTER TL-D Super 80 70W/840 SLV/25

The MASTER TL-D Super 80 lamp offers more lumens per watt and better color rendering than TL-D standard colors. Furthermore, it has a lower mercury content. The lamp can be operated in existing TL-D luminaires.

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information				
Cap-Base	G13 [Medium Bi-Pin Fluorescent]			
Flux measurement reference	Sphere			
Life to 50% Failures (Nom)	15,000 hour(s)			
Light Technical				
Color Code	840 [CCT of 4000K]			
Luminous Flux	6,200 lm			
Color Designation	Cool White (CW)			
Chromaticity Coordinate X (Nom)	0.38			
Chromaticity Coordinate Y (Nom)	0.38			
Correlated Color Temperature (Nom)	4000 K			
Luminous Efficacy (rated) (Nom)	89 lm/W			
Color rendering index (CRI)	81			
Operating and Electrical				
Power Consumption	70.0 W			

Lamp Current (Nom)	0.690 A
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	Т8
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) Content (Max)	3 mg
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	70 kWh
EPREL Registration Number	423436
Product Data	
Order product name	MASTER TL-D Super 80 70W/840 SLV/25


Datasheet, 2024, February 13 data subject to change

MASTER TL-D Super 80

Full product name	MASTER TL-D Super 80 70W/840 SLV/25			
Full product code	871150061592340			
Order code	927923884014			
Material Nr. (12NC)	927923884014			
Numerator - Quantity Per Pack	1			


EAN/UPC - Product/Case	8711500615923		
Numerator - Packs per outer box	25		
EAN/UPC - Case	8711500615930		

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80	28 mm	1,763.8 mm	1,770.9 mm	1,768.5 mm	1,778 mm
70W/840 SLV/25					


Photometric data



Spectral Power Distribution Colour - MASTER TL-D Super 80 70W/840 SLV/25

Lifetime






Life Expectancy Diagram - MASTER TL-D Super 80 70W/840 SLV/25

Life Expectancy Diagram - MASTER TL-D Super 80 70W/840 SLV/25

MASTER TL-D Super 80

Lifetime



Lumen Maintenance Diagram - MASTER TL-D Super 80 70W/840 SLV/25

