



MASTER TL5 High Efficiency

MASTER TL5 HE 14W/830 1SL/40

Low-pressure mercury discharge lamps with a tubular 16 mm envelope

Product data

General Information		LLMF 2000 h Rated		96 %	
Cap base	G5 [G5]	LLMF 4000 h Rated	95 %		
Life to 50% failures preheat (nom.)	24000 h	LLMF 6000 h Rated	94 %		
Features	na [Not Applicable]	LLMF 8000 h Rated	93 %		
System description	High Efficiency	LLMF 12000 h Rated	92 %		
LSF Preheat 2000 h Rated	99 %	LLMF 16000 h Rated	91 %		
LSF Preheat 4000 h Rated	99 %	LLMF 20000 h Rated	90 %		
LSF Preheat 6000 h Rated	99 %				
LSF Preheat 8000 h Rated	99 %	Operating and Electrical			
LSF Preheat 16000 h Rated	97 %	Power (Rated) (Nom)	14 W		
LSF Preheat 20000 h Rated	84 %	Lamp current (nom.)	0.165 A		
Light Technical		Temperature			
Colour code	830 [CCT of 3,000 K]	Design temperature (nom.)	35 °C		
Luminous flux (nom.)	1350 lm				
Luminous flux (rated) (nom.)	1200 lm	Controls and Dimming			
Colour designation	Warm white (WW)	Dimmable	yes		
Luminous efficacy (@ max. lumen, rated) (nom.)	99 lm/W				
Correlated colour temperature (nom.)	3000 K	Mechanical and Housing			
Luminous efficacy (rated) (nom.)	86 lm/W	Cap base information	Green Plate		
Color rendering index (max.)	85				
Color rendering index (min.)	80	Approval and Application			
Color rendering index (nom.)	>80	Energy efficiency label (EEL)	A+		

MASTER TL5 High Efficiency


Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	15 kWh
Product Data	
Full product code	871150063938755
Order product name	MASTER TL5 HE 14W/830 SLV/40
EAN/UPC – product	8711500639387
Order code	63938755

Local Code	14830
Numerator – quantity per pack	1
Numerator – packs per outer box	40
Material no. (12NC)	927926083055
Net weight (piece)	52.000 g
ILCOS Code	FDH-14/30/1B-L/P-G5-16/550

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




TL5 14W/830/GP HE

Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE 14W/830 SLV/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm

Photometric data



Lightcolour /830



Lightcolour /830

MASTER TL5 High Efficiency

Lifetime

