



MASTER PL-S 2 Pin

MASTER PL-S 9W/827/2P 1CT/10

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

Warnings and Safety

- \cdot Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information			
Cap-Base	G23		
Life to 50% Failures (Nom)	10,000 hour(s)		
Light Technical			
Color Code	827 [CCT of 2700K]		
Luminous Flux	600 lm		
Color Designation	Incandescent White		
Correlated Color Temperature (Nom)	2700 K		
Luminous Efficacy (rated) (Nom)	67 lm/W		
Color rendering index (CRI)	82		

Operating and Electrical	
Power Consumption	8.7 W
Lamp Current (Nom)	0.170 A
Controls and Dimming	
Dimmable	No
Approval and Application	
Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	11 kWh


Datasheet, 2023, April 14 data subject to change

MASTER PL-S 2 Pin

Product Data	
Order product name	MASTER PL-S 9W/827/2P 1CT/10
Full product name	MASTER PL-S 9W/827/2P 1CT/10
Full product code	871869960700500
Order code	927936082765
Material Nr. (12NC)	927936082765


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699607005
Numerator - Packs per outer box	10
EAN/UPC - Case	8718699607012

Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-S 9W/827/2P 1CT/10	28 mm	13 mm	129 mm	145 mm	167 mm


Photometric data



Spectral Power Distribution Colour - MASTER PL-S 9W/827/2P 1CT/10

Lifetime






Life Expectancy Diagram - MASTER PL-S 9W/827/2P 1CT/10

Life Expectancy Diagram - MASTER PL-S 9W/827/2P 1CT/10

MASTER PL-S 2 Pin

Lifetime



Lumen Maintenance Diagram - MASTER PL-S 9W/827/2P 1CT/10



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.