



# PL-Q 2 Pin

## PL-Q 16W/827/2P 1CT/10BOX

Compact fluorescent lamps with a quadrant-like shape

### Product data

General Information	
Cap base	GR8 [ GR8]
Life to 10% failures (nom.)	6000 h
Life to 50% failures (nom.)	8000 h
LSF 2000 h Rated	99 %
LSF 4000 h Rated	96 %
LSF 6000 h Rated	89 %
LSF 8000 h Rated	73 %
Light Technical	
Colour Code	827 [ CCT of 2,700 K]
Lamp Luminous Flux 25°C EL (Nom)	1050 lm
Lamp Luminous Flux (Nom)	1050 lm
Colour Designation	Incandescent White
Colour Temperature, horizontal (Nom)	2700 K
Lamp Luminous Efficacy EM (Nom)	66.6 lm/W
Colour Rendering Index, horiz (Nom)	82
LLMF 2000 h Rated	90 %
LLMF 4000 h Rated	85 %
LLMF 6000 h Rated	82 %
LLMF 8000 h Rated	80 %
LLMF 12000 h Rated	79 %
LLMF 16000 h Rated	78 %
LLMF 20000 h Rated	77 %

Operating and Electrical	
Power (Rated) (Nom)	16.0 W
Lamp current (nom.)	0.196 A
Temperature	
Design temperature (nom.)	25 °C
Controls and Dimming	
Dimmable	no
Mechanical and Housing	
Cap base information	2P
Approval and Application	
Energy efficiency label (EEL)	B
Mercury (Hg) content (nom.)	4.0 mg
Energy Consumption kWh/1000 h	20 kWh
Product Data	
Full product code	871150026965225
Order product name	PL-Q 16W/827/2P 1CT/10BOX
EAN/UPC – product	8711500269652
Order code	927939082740
Local Code	PLQ16W8272P
Numerator – quantity per pack	1
Numerator – packs per outer box	10

# PL-Q 2 Pin

Material no. (12NC)	927939082740
Net weight (piece)	68.000 g
ILCOS Code	FSS-16/27/1B-I-GR8



## Warnings and Safety

## Dimensional drawing

Product	U (max)	D (max)	D1 (max)	C (max)	C1 (max)	F (max)	E (max)
PL-Q 16W/ 827/2P 1CT/ 10BOX	40 mm	13.7 mm	27.0 mm	138 mm	49 mm	40.5 mm	135 mm

### PL-Q 16W/827/2P



## Photometric data



### Lightcolour /827

### Lightcolour /827

## Lifetime




### LDLE\_PLQ2P\_0001-Life expectancy diagram

### LDLE\_PLQ2P\_0002-Life expectancy diagram

## PL-Q 2 Pin

### Lifetime



LDLM\_PLQ2P\_0001-Lumen maintenance diagram

