

# MASTER TL5 High Output Eco

## MASTER TL5 HO Eco 73=80W/840 UNP/40

This extremely efficient TL5 lamp (tube diameter 16 mm) saves considerable energy by simple lamp-for-lamp replacement. The TL5 HO Eco lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and colour rendering. Application areas vary from offices and industry to schools and retail environments.

### Product data

General Information	
Cap base	G5 [ G5]
Life to 50% failures preheat (nom.)	30000 h
Features	na [ Not Applicable]
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
LSF Preheat 16000 h Rated	99 %
LSF Preheat 20000 h Rated	94 %
Light Technical	
Colour code	840 [ CCT of 4,000 K]
Luminous flux (nom.)	7000 lm
Luminous flux (rated) (nom.)	6550 lm
Colour designation	Cool White (CW)
Luminous efficacy (@ max. lumen, rated) (nom.)	95 lm/W
Correlated colour temperature (nom.)	4000 K
Luminous efficacy (rated) (nom.)	89 lm/W

Color rendering index (max.)	85
Color rendering index (min.)	80
Color rendering index (nom.)	82
LLMF 2000 h Rated	96 %
LLMF 4000 h Rated	95 %
LLMF 6000 h Rated	94 %
LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %

Operating and Electrical	
Power (Rated) (Nom)	73.3 W
Lamp current (nom.)	0.550 A
Temperature	
Design temperature (nom.)	35 °C

# MASTER TL5 High Output Eco

## Controls and Dimming

Dimmable	yes
----------	-----

## Approval and Application

Energy efficiency label (EEL)	A+
Mercury (Hg) content (nom.)	1.4 mg
Energy Consumption kWh/1000 h	80 kWh


## Product Data

Full product code	872790082597800
Order product name	MASTER TL5 HO Eco 73=80W/840 UNP/40

EAN/UPC – product	8711500880093
Order code	82597800
Local Code	73840TL5ECO
Numerator – quantity per pack	1
Numerator – packs per outer box	40
Material no. (12NC)	927991884031
Net weight (piece)	127.400 g
ILCOS Code	FDH-73/40/1B-L/P-G5-16/1450

## Warnings and Safety


## Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO Eco 73=80W/840 UNP/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm

## TL5 HO Eco 73=80W/840

## Photometric data




## Lightcolour /840




## Lightcolour /840

# MASTER TL5 High Output Eco

## Lifetime



LDLE\_TL5ECO\_0001-Life expectancy diagram



LDLM\_TL5ECO\_0001-Lumen maintenance diagram

