



Actinic BL TL-E

Actinic BL TL-E 22W/10 1CT/20

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers.

Product data


General Information	
Cap base	G10Q [G10q]
Main application	Insect traps
Life to 50% failures (nom.)	9000 h
Useful life (nom.)	4000 h
Light Technical	
Colour code	10
Colour designation	Ultra Violet A
Depreciation at 500 Hours	15 %
Depreciation at 500 Hours	25 %
Operating and Electrical	
Power (Rated) (Nom)	22 W
Lamp current (nom.)	0.4 A
Voltage (Nom)	62 V
Approval and Application	
Mercury (Hg) content (nom.)	8 mg

UV	
UV-B/UV-A (IEC)	0.1 %
UV-A radiation 100 hours (IEC)	3.9 W
Product Data	
Full product code	871150028513305
Order product name	Actinic BL TL-E 22W/10 1CT/20
EAN/UPC – product	8711500285133
Order code	28513305
Numerator – quantity per pack	1
Numerator – packs per outer box	20
Material no. (12NC)	928026201005
Net weight (piece)	0.110 kg

Actinic BL TL-E

Warnings and Safety



Dimensional drawing



Product	D (max)	D (min)	F (max)	F (min)	E (min)	E (max)
Actinic BL TL-E 22W/10 1CT/20	30.9 mm	26.2 mm	155.6 mm	149.1 mm	205.0 mm	213.5 mm

TL-E 22W/10

Photometric data



XDPO_XURTLE_10-Spectral power distribution Colour

