



MASTER TL-E Circular Super 80

TL-E 40W/865 1CT/12

This circular TL lamp (tube diameter 29 mm) enables omni-directional light distribution. It is suitable for use in a wide range of luminaires for various purposes, including decorative ones, in 'human' applications such as schools, offices, shops and homes, and for lighting of residential areas.

Product data

General Information	
Cap-Base	G10Q [G10q]
Life to 50% Failures (Nom)	13000 h
LSF 2000 h Rated	98 %
LSF 4000 h Rated	77 %
LSF 6000 h Rated	60 %
LSF 8000 h Rated	45 %
Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux (Nom)	3070 lm
Luminous Flux (Rated) (Nom)	3070 lm
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	78 lm/W
Color Rendering Index (Nom)	80
LLMF 2000 h Rated	89 %
LLMF 4000 h Rated	84 %
LLMF 6000 h Rated	81 %

LLMF 8000 h Rated	80 %
Operating and Electrical	
Power (Nom)	40.0 W
Lamp Current (Nom)	0.420 A
Voltage (Nom)	110 V
Temperature	
Design Temperature (Nom)	25 °C
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	8 mg
Energy Consumption kWh/1000 h	44 kWh
Product Data	
Full product code	872790084057500


MASTER TL-E Circular Super 80

Order product name	TL-E 40W/865 1CT/12
EAN/UPC - Product	8727900840575
Order code	928027486570
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

Material Nr. (12NC)	928027486570
Net Weight (Piece)	0.250 kg
ILCOS Code	FSC-40/65/1B-E-G10q-29/400

Warnings and Safety

Dimensional drawing



TL-E 40W/865

Product

TL-E 40W/865 1CT/12

