



MASTER HPI-T Plus

MASTER HPI-T Plus 250W/645 E40 1SL

Quartz metal halide lamps with clear outer bulb

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- For use with control gear designed for high-pressure mercury or sodium lamps
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information					
Cap-Base	E40 [E40]				
Operating Position	P20 [Parallel +/-20D or Horizontal(HOR)]				
Life to 50% Failures (Nom)	20,000 hour(s)				
Light Technical					
Color Code	645 [CCT of 4500K]				
Color Designation	Cool White (CW)				
Chromaticity Coordinate X (Nom)	365				
Chromaticity Coordinate Y (Nom)	377				
Correlated Color Temperature (Nom)	4500 K				
Luminous Efficacy (rated) (Nom)	84 lm/W				
Color rendering index (CRI)	65				
Arc Length O (Nom)	29 mm				
Operating and Electrical					
Power Consumption	245 W				
Voltage (Nom)	128 V				

Voltage (Nom)	128 V				
Controls and Dimming					
Dimmable	No				
Mechanical and Housing					
Bulb Finish	Clear				
Bulb Shape	T46 [T 46mm]				
Approval and Application					
Mercury (Hg) Content (Nom)	33 mg				
Energy Consumption kWh/1000 h	269 kWh				
Product Data					
Order product name	MASTER HPI-T Plus 250W/645 E40 1SL				
Full product name	MASTER HPI-T Plus 250W/645 E40 1SL				
Full product code	871016314600300				
Order code	928076109299				


Datasheet, 2023, April 16 data subject to change

MASTER HPI-T Plus

Material Nr. (12NC)	928076109299
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163146003
Numerator - Packs per outer box	12


EAN/UDC Coop	07070000777F0
EAN/UPC - Case	8727900077759


Dimensional drawing




Product	D (max)	0	L	C (max)
MASTER HPI-T Plus 250W/645 E40 1SL	47 mm	29 mm	155 mm	255 mm

Photometric data









Light Distribution Diagram - MASTER HPI-T Plus 250W/645 E40 1SL

Spectral Power Distribution Colour - MASTER HPI-T Plus 250W/645 E40 1SL

Lifetime





Life Expectancy Diagram - MASTER HPI-T Plus 250W/645 E40 1SL

Lumen Maintenance Diagram - MASTER HPI-T Plus 250W/645 E40 1SL

MASTER HPI-T Plus



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.