



MSR Hot Restrike

MSR 250 HR 1CT/4

Thanks to an optimized color temperature and a high color rendering index, the MSR Hot Restrike creates perfect 'daylight' in any condition. Also, the single ended lamp design enables hot re-ignition, which ensures daylight lighting and superb color rendition is always instantly available. They also incorporate the innovative P3 technology, developed by Philips, which allows use at higher temperatures and therefore extends lifetime and consistency of high-quality light output.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information	
Cap-Base	GZY9.5 [GZY9.5]
Operating Position	UNIVERSAL [Any or Universal (U)]
Life to 50% Failures (Nom)	750 hour(s)
Light Technical	
Color Code	- [Not Specified]
Luminous Flux (Min)	18,500 lm
Luminous Flux	20,000 lm
Chromaticity Coordinate X (Nom)	309
Chromaticity Coordinate Y (Nom)	320
Correlated Color Temperature (Nom)	6000 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Color rendering index (CRI)	90
Arc Length O (Nom)	5.0 mm

Operating and Electrical	
Power Consumption	250 W
Lamp Current (Nom)	2.6 A
Controls and Dimming	
Dimmable	No
Product Data	
Order product name	MSR 250 HR 1CT/4
Full product name	MSR 250 HR 1CT/4
Full product code	871869641602000
Order code	928175605115
Material Nr. (12NC)	928175605115
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696416020
Numerator - Packs per outer box	4

MSR Hot Restrike


EAN/UPC - Case	8718696416037
----------------	---------------

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 250	23 mm	5.0	58 mm	60 mm	59	110 mm	24 mm	23.5	23 mm
HR 1CT/4		mm			mm			mm	

Photometric data



Spectral Power Distribution Colour - MSR 250 HR 1CT/4

