



TrueForce LED Industrial and Retail Mains (Highbay – HPI/SON/HPL)

TrueForce LED HB MV ND 200-160W E40 840 WB

Philips TrueForce LED Industrial & Retail mains lamps offer an easy and short payback LED solution to replace High Intensity Discharge (HID) lamps. The products bring the energy-efficiency and long lifetime benefits of LED to HID replacement and provide instant savings and low initial investment. With the right lamp size and light distribution, you can easily retrofit TrueForce LED I&R mains lamps and bypass the existing ballast while enhancing the lighting quality.

Product data

| General Information | |
|-------------------------------|--------------------|
| Cap base | E40 [E40] |
| Nominal lifetime | 50,000 h |
| Switching Cycle | 50,000 |
| Lighting Technology | LED |
| EU RoHS compliant | Yes |
| | |
| Light Technical | |
| Colour Code | 840 [CCT of 4000K] |
| Beam angle (nom.) | 120 degree(s) |
| Luminous Flux | 20,000 lm |
| Colour designation | Cool White (CW) |
| Correlated Colour Temperature | 4000 K |

| Luminous efficacy (rated) (nom.) | 125.00 lm/W |
|--------------------------------------|------------------|
| Colour consistency | <6 |
| Colour rendering index (CRI) | 80 |
| LLMF at end of nominal lifetime (nom | a.) 70 % |
| | |
| Operating and Electrical | |
| Line Frequency | 50 to 60 Hz |
| Input frequency | 50 to 60 Hz |
| Power Consumption | 160 W |
| Lamp current (nom.) | 900 mA |
| Starting time (nom.) | 0.7 s |
| Warm-up time to 60% light | 0.7 s |
| Power Factor (Fraction) | 0.9 |


Datasheet, 2023, April 29 data subject to change

TrueForce LED Industrial and Retail Mains (Highbay - HPI/SON/HPL)

| Voltage (nom.) | 220-240 V | |
|---------------------------------|---------------|--|
| | | |
| Temperature | | |
| T-Case maximum (nom.) | 100 °C | |
| | | |
| Controls and Dimming | | |
| Dimmable | No | |
| | | |
| Mechanical and Housing | | |
| Lamp Finish | Frosted | |
| Bulb shape | T50 [T 50 mm] | |
| | | |
| Approval and Application | | |
| Energy consumption kWh/1 000 ho | ure 160 kWh | |


| TForce LED HB MV ND 200-160W E40 840 WB |
|---|
| TrueForce LED HB MV ND 200-160W E40 840 |
| WB |
| 871869959672900 |
| 59672900 |
| 929001812502 |
| 1 |
| 8718699596729 |
| 2 |
| 8718699596736 |
| |

Dimensional drawing




| Product | D | С |
|---|--------|--------|
| TForce LED HB MV ND 200-160W E40 840 WB | 211 mm | 263 mm |

Photometric data








Light Distribution Diagram - TForce LED HB MV ND 200-160W E40 840 WB


TrueForce LED Industrial and Retail Mains (Highbay - HPI/SON/HPL)


Photometric data



Spectral Power Distribution Colour - TForce LED HB MV ND 200-160W E40 840 WB


Lifetime





Life Expectancy Diagram - TForce LED HB MV ND 200-160W E40 840 WB

Life Expectancy Diagram - TForce LED HB MV ND 200-160W E40 840 WB



Lumen Maintenance Diagram - TForce LED HB MV ND 200-160W E40 840 WB

TrueForce LED Industrial and Retail Mains (Highbay - HPI/SON/HPL)



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.