



LED MR16

8.5MR16/LED/830/F35/DIM 12V 10/1FB

Philips LED MR-16 lamps with single optic technology provide the look and color quality of traditional halogens while using a fraction of the energy. A perfect fit for spot lighting, they are compatible with most existing fixtures with MR16 GU5.3 holders and are designed as a retrofit replacement for halogen or incandescent spots.

Product data

General Information	
Cap-Base	GU5.3 [GU5.3]
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	35 degree(s)
Luminous Flux	620 lm
Luminous Intensity (Nom)	1,700 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	72.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
	-
Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz

Power Consumption	8.5 W
Lamp Current (Nom)	960 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	100 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Aluminum
Bulb Shape	MR16 [2inch/50mm]
Approval and Application	
Suitable For Accent Lighting	Yes


Datasheet, 2023, November 12 data subject to change

LED MR16

Energy Consumption kWh/1000 h	- kWh	
Product Data		
Order product name	8.5MR16/LED/830/F35/DIM 12V 10/1FB	
Full product name	8.5MR16/LED/830/F35/DIM 12V 10/1FB	
Order code	929001881704	
Material Nr. (12NC)	929001881704	


Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677533199
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677533194

Dimensional drawing



Product	D	С
8.5MR16/LED/830/F35/DIM 12V 10/1FB	50.5 mm	46.5 mm


Photometric data



Calculus Photometrics 4.5 Philips Lighting B.V. Page: UT

,,,,

Accent Lighting Spots - 8.5MR16/LED/830/F35/DIM 12V 10/1FB




Light Distribution Diagram - 8.5MR16/LED/830/F35/DIM 12V 10/1FB

Spectral Power Distribution Colour - 8.5MR16/LED/830/F35/DIM 12V 10/1FB

LED MR16

Lifetime



Lumen Maintenance Diagram - 8.5MR16/LED/830/F35/DIM 12V 10/1FB

Life Expectancy Diagram - 8.5MR16/LED/830/F35/DIM 12V 10/1FB



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.