

TROFFER LENS OPTIONS

| Brand | Lens | Thickness | GC8 | GR8 |
|---------|-----------------------|-----------|-----|-----|
| Generic | A | 0.095 | X | X |
| | A125 | 0.125 | X | X |
| | A125MIN | .125 min | X | X |
| | A125/RFI (since 1980) | 0.125 | X | X |
| | A19/156 | 0.156 | X | X |
| | A19/187 | 0.187 | X | |
| KSH | K12/125 | 0.125 | X | |
| | A19/156 | 0.156 | X | X |
| | KSH23/125 | 0.125 | X | |

NOTES: **Inverted Lens** - For inverted lens add "INV" to lens description. (Not available for GR8/GR5). **3.** For additional lens options consult factory.

PARABOLICS, RECESSED AND SURFACE EMERGENCY OPTIONS

| Brand | Battery | RDI | GC8 | GR8 | AC | WN | BC ⁶ |
|-----------|--|-----|----------------|----------------|----------------|----|-----------------|
| Generic | EL4 (350-500 lm) | X | X | X | X | X | X |
| | EL5 (up to 700 lm) | X | | X | X | X | X |
| | EL8 | X | X | X | X | X | X |
| | EL5HO (up to 600 lm) | X | | X | X | X | X |
| | EL14 (600-1400 lm) ¹ | X | X | X | X | X | X |
| Bodine | EL-B100 (350-450 lm) | X | X ⁴ | X ⁴ | X | X | X |
| | EL-B90 (500-600 lm) | X | X ⁴ | X ⁴ | X | X | X |
| | EL-B70A (600-700 lm) | X | X ⁴ | X ⁴ | X | | X |
| | EL-B60 (600-700 lm) | X | X ⁴ | X ⁴ | X | X | X |
| | EL-B50 (1100-1400 lm) ^{1,2} | X | X ⁴ | X ⁴ | X | | X |
| | EL-B50ST (1100-1400 lm) ^{1,2} | X | X ⁴ | X ⁴ | X | | X |
| | EL-LP550 (390-700 lm) | X | | X | X ⁵ | | |
| | EL-LP600 (600-1325 lm) | X | | X | X ⁵ | | |
| Iota | EL-I32 (up to 550 lm) | X | X | X | X | X | X |
| | EL-I40 (up to 700 lm) | X | X | X | X | X | X |
| | EL-I320 (1300 lm) ^{1,2} | X | X ⁴ | X ⁴ | X | | X |
| | EL-I232 (2 @ 1400 lm) ² | X | X ⁴ | X ⁴ | X | | X |
| | EL-ISD80 (1300 lm) ^{1,2} | X | X ⁴ | X ⁴ | X | | X |
| | EL-ISL28 (up to 500 lm) ³ | X | | X | X ⁵ | | |
| | EL-ISL54 (up to 825 lm) | X | | X | X ⁵ | | |
| | EL-ISL540 (up to 1300 lm) | X | | X | X ⁵ | | |
| Sure-Lite | EBP450X | | | | | | |
| | EBP700X | | | | | | |
| | EBP1400NCF(1400lm) ^{2,3} | X | X ⁴ | X ⁴ | X ⁴ | | X |

NOTES: **1.** For battery wired for two lamps, specify "/2L" after battery description. **2.** Due to size, battery cannot be installed in 2-lamp and 4-lamp 2' x 2's, except RDI. **3.** Will not operate two (2) lamps. **4.** Due to battery size, a wide ballast cover is used. **5.** 2' x 4' only. **6.** Due to size limitations, battery cannot be installed in two foot (2') units.

PRODUCT INFORMATION FOR EXTENDED OPTIONS

| Nomenclature | Description | EP3 | GC8 | GR8 | RDI | AC |
|------------------|---|----------------|----------------|----------------|-----|-----------------|
| LAP ¹ | Less Access Plate | X | X | X | | X |
| LAO ² | Less Access Opening | X | X | X | | X |
| FR | Suitable for Install Fire Rated Ceiling | X | X | X | X | X |
| IC | IC-Rated ⁶ | X | X | X | X | X ¹⁰ |
| G1 | Gasket btw DR Frm and Housing | | X | X | | |
| G2 ³ | Gasket btw DR Frm and Housing, btw Lens and DR Frm | | X ⁵ | | | |
| G3 ³ | Gasket btw DR Frm and Hous, btw Lens and DR Frm on Mnt Surf of Trm | | X ⁵ | | | |
| MEP ⁴ | Modified End Plate | X | | | | |
| REP | Riveted End Plate | X | X | | X | |
| 6/LC | Six (6) Lens Clips | | X | | | |
| 2BC | Second Ballast Cover | X ⁷ | X ⁸ | X ⁸ | | |
| EM/BC | EM Installed in field ⁹ (Wide or standard BC used in fixture) | X | X | X | | |
| 1IN/MLAB | One Inch (1") Mark Labeling | X | X | | X | |
| 2IN/MLAB | Two Inch (2") Mark Labeling | X | X | | X | |
| PAF | Painted After Fabrication | X | X | | | |
| DS | Debris Shield | | | | X | |

NOTES: **1.** Option used when housing access plates are shipped ahead for pre-wiring. **2.** Required for 2-lamp or 4-lamp 2' x 2' fixture when two (2) ballast or one (1) ballast and emergency are requested. **3.** Aluminum door and minimum 0.125" shielding. **4.** Installation requires end fillers and may require end support bracket. See accessory page for further details. **5.** Aluminum doorframe (FA/RA) only. **6.** See product spec sheet for limitations. **7.** For 2' x 2' 3L, 2BC is standard. See product spec sheet for additional info. **8.** For 2' x 2' 3L Biax or U1-5/8, 2BC is standard; 2U6T8, 3T5 or 3T8, 2BC is optional. **9.** Refer to EM table above for fit. **10.** AC only.

PACKAGING (REQUIRED)

| Nomenclature | Description | EP3 | GC8 | GR8 | AC |
|--------------|-------------------------|-----|-----|-----|----|
| U | Unit Pack | X | X | X | X |
| PAL | Job Pack, out of carton | X | X | | |
| PALC | Job Pack, in carton | X | X | | X |