



Project: \_\_\_\_\_

Location: \_\_\_\_\_

Cat.No: \_\_\_\_\_

Type: \_\_\_\_\_

Lamps: \_\_\_\_\_ Qty: \_\_\_\_\_

Notes: \_\_\_\_\_

Complete Fixture consists of Reflector Trim & Frame-In Kit. Select each separately.

Reflector Trim - Eyeball	Frame-In Kit — See Individual Frame-In Kit Specification Sheets			
	Incandescent			
	Frame-In Kit	Installation Type	Lamping	Height
1082 Perma White Finish	1002P1	Non-IC	50W PAR20	6 7/8"
	1003R	Non-IC Remodeler	75W R20	6 7/8"
	1000IC	IC	50W PAR20	7 5/16"
	1000AICM	AirSeal® IC	75W R20	7 5/16"
	1004IC/N	AirSeal® IC		7 1/2"
	1004ICR	IC Remodeler		7 1/2"
	1004ICX/N	AirSeal® IC		7 1/4"
	1004IC/N	Non-IC	50W PAR20	7 1/2"
	1004ICR	Non-IC Remodeler	75W R20	7 1/2"

### Features

- Housing: Aluminum, .040" (18 ga.); Perma White trim flange.
- Eyeball: Die-formed, one piece, aluminum, .040" (18 ga.); provides 360° horizontal rotation and 0° to 45° vertical adjustment; non-yellowing, scratch resistant Perma White finish.
- Frame-In Kit: (1002P1 standard frame shown). Other frames listed above and shown on the right. See Frame-In Kit specification sheets for more details.

### Options & Accessories

Retaining Clips: 1955 - For installing in existing ceiling

### Labels

UL (Suitable for Damp Locations), L.B.E.W.

