



Project: \_\_\_\_\_

Location: \_\_\_\_\_

Cat.No: \_\_\_\_\_

Type: \_\_\_\_\_

Lamps: \_\_\_\_\_ Qty: \_\_\_\_\_

Notes: \_\_\_\_\_

Reflector Trim	Frame-In Kit - See Individual Frame-In Kit Specification Sheets			
	Incandescent			
	Frame-In Kit	Installation Type	Lamping	Height
1088 Matte Black Baffle	1004IC/N	Non-IC	75W PAR30 Sylvania short neck only	7 1/2"
1088WH Matte White Baffle	1004ICR	Non-IC Remodeler		7 1/2"
1088GW Gloss White Baffle	1004IC/N	IC	50W PAR30	7 1/2"
	1004ICR	IC Remodeler		7 1/2"

## Features

- Housing:** Aluminum, .032 (18 ga.) Beveled trim flange.
- Eyeball:** Formed, one piece aluminum, .032 (18 ga.); provides 0° to 30° vertical adjustment; non-yellowing, scratch resistant finish.
- Frame-In Kit:** (1004IC standard frame shown). Other frame shown on the right. See Frame-In Kit specification sheets for more details.

## Labels

UL Listed. Suitable for Damp Locations.

# 1088 Lytecaster CFL 5"

## Regressed Adjustable Trim

Lighting Performance Data		Narrow				Medium				Wide			
DISTANCE 0' 1' 2' 3' 4' 5' 6'	FOOTCANDLES (On Beam Center At 6')	50W PAR30 NSP (T-H)		75W PAR30 NSP (T-H)		50W PAR30 NFL (T-H)		75W PAR30 NFL (T-H)		50W PAR30 FL (T-H)		75W PAR30 FL (T-H)	
		181		291		49		83		31		50	
BEAM SPREAD (To 50% Max. CP)		12"		12"		32"		32"		42"		42"	
MAX. CANDLEPOWER (Candelas)		6,500		10,500		1,750		3,000		1,100		1,800	
RATED LIFE (Hours)		2,000		2,000		2,000		2,000		2,000		2,000	
0° AIMING ANGLE Illumination on Horizontal Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W
		6'	181	1.3'	1.3'	8'	164	1.7'	1.7'	4'	109	2.3'	2.3'
		8'	102	1.7'	1.7'	12'	73	2.5'	2.5'	6'	49	3.4'	3.4'
		10'	65	2.1'	2.1'	16'	41	3.4'	3.4'	8'	27	4.6'	4.6'
30° AIMING ANGLE Illumination on Horizontal Plane		12'	45	2.5'	2.5'	20'	26	4.2'	4.2'	10'	17	5.7'	5.7'
		12'	45	2.5'	2.5'	20'	26	4.2'	4.2'	10'	17	5.7'	5.7'
		12'	45	2.5'	2.5'	20'	26	4.2'	4.2'	10'	17	5.7'	5.7'
		12'	45	2.5'	2.5'	20'	26	4.2'	4.2'	10'	17	5.7'	5.7'
30° AIMING ANGLE Illumination on Vertical Plane		D	FC	L	W	D	FC	L	W	D	FC	L	W
		5'	169	1.4'	1.2'	7'	139	2.0'	1.7'	3'	126	2.4'	2.0'
		7'	86	2.0'	1.7'	10'	68	2.8'	2.4'	5'	45	3.9'	3.3'
		9'	52	2.5'	2.2'	13'	40	3.7'	3.2'	7'	23	5.5'	4.6'
30° AIMING ANGLE Illumination on Vertical Plane		11'	35	3.1'	2.7'	16'	27	4.5'	3.9'	9'	14	7.1'	6.0'
		11'	35	3.1'	2.7'	16'	27	4.5'	3.9'	9'	14	7.1'	6.0'
		11'	35	3.1'	2.7'	16'	27	4.5'	3.9'	9'	14	7.1'	6.0'
		11'	35	3.1'	2.7'	16'	27	4.5'	3.9'	9'	14	7.1'	6.0'

Data are based on bare lamp photometrics.  
FC is initial footcandles at center of beam. L and W are to the point that the candlepower drops 50% of maximum

Beam Center Location											
	Distance D (ft.)	1	2	3	4	5	6	7	8	9	10
	Distance C (ft.)	1.7	3.5	5.2	6.9	8.7	10.4	12.1	13.8	15.6	17.3
This chart locates the distance (C) to the center of the light beam for various distances (D) when the lamp is aimed 30° from vertical, the preferred aiming angle for lighting pictures on a wall											



© 2020 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Signify North America Corporation  
200 Franklin Square Drive,  
Somerset, NJ 08873  
Telephone 855-486-2216

Signify Canada Ltd.  
281 Hillmount Road,  
Markham, ON, Canada L6C 2S3  
Telephone 800-668-9008

All trademarks are owned by Signify Holding or their respective owners.