Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's | name o | or trade | mark: | PHILIPS |
|------------|--------|----------|-------|---------|
|------------|--------|----------|-------|---------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Model identifier: | 9290024693 |
|-------------------|------------|
|-------------------|------------|

| _ | • | | | |
|------|-----|--------|--------|----|
| Tyna | Ot. | liaht | source | ٥. |
| IVDC | OI. | IIGIIL | Souic | ᠸ. |

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|-----|---------------------------------|---------------------------------|
| Light source cap-type | B22 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | Yes |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Only with spe- cific dimmers |

Product parameters

| Product parameters | | | | | |
|---|--|---------------------------|--|--------------|--|
| Parameter | | Value | Parameter | Value | |
| | General product parameters: | | | | |
| | nption in on- 00 h), rounded st integer | 10 | Energy efficiency class | F | |
| dicating if it refe a sphere (360º) | s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º) | 1 055 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 | |
| On-mode pow pressed in W | ver (P _{on}), ex- | 9,5 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | 0,43 | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 | |
| Outer dimen- | Height | 61 | Spectral power dis- | See image | |
| sions without | Width | 110 | tribution in the | in last page | |
| separate con- trol gear, light- | Depth | 110 | range 250 nm to 800 nm, at full-load | | |

| ing control parts and non- lighting con- trol parts, if any (millime- tre) | | | | |
|---|------|--|----------------|--|
| Claim of equivalent power ^(a) | Yes | If yes, equivalent power (W) | 75 | |
| | | Chromaticity coordinates (x and y) | 0,458 0,410 | |
| Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value 0 Survival factor 0,90 | | | 0,90 | |
| the lumen maintenance factor | 0,96 | | | |
| Parameters for LED and OLED mains light sources: | | | | |
| displacement factor (cos φ1) | 0,70 | Colour consistency in McAdam ellipses | 6 | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | | If yes then replace- ment claim (W) | - | |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 0,4 | |

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

