Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's | name or | trade mark: | PHILIPS |
|------------|---------|-------------|---------|
|------------|---------|-------------|---------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Model identifier: | 9290030037 |
|-------------------|------------|
|-------------------|------------|

| Type | of I | ight | sour | ce: |
|------|--------------|-------|------|-----|
| IVDC | U I I | ISIIL | JUUI | ··· |

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|-----|---------------------------------|------|
| Light source cap-type | E27 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |

Product parameters

| Parameter | | Value | Parameter | Value |
|---|--|---------------------------|--|--------------|
| | | General product p | arameters: | <u> </u> |
| ٠, | nption in on- 00 h), rounded st integer | 13 | Energy efficiency class | E |
| dicating if it refe a sphere (360°) | s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º) | 1 521 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 13,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 90 |
| Outer dimen- | Height | 110 | Spectral power dis- | See image |
| sions without | Width | 60 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 60 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|---|--|--|----------------|--|--|
| Claim of equivalent power ^(a) | Yes | If yes, equivalent power (W) | 100 | | |
| | | Chromaticity coordinates (x and y) | 0,458 0,410 | | |
| Parameters for LED and OLED I | Parameters for LED and OLED light sources: | | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 | | |
| the lumen maintenance factor | 0,93 | | | | |
| Parameters for LED and OLED r | nains light sources: | | | | |
| displacement factor (cos φ1) | 0,71 | Colour consistency in McAdam ellipses | 6 | | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | | If yes then replace- ment claim (W) | - | | |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 0,4 | | |

(a)'-': not applicable; (b)'-': not applicable;

