## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

_	•			
Type	Λt	liaht	COLLE	ro.
IVDE	UI.	HEIIL	30ui	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	E27			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				

## **Product parameters**

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consun mode (kWh/10 up to the neares	00 h), rounded	4	Energy efficiency class	А		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		840 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P <sub>on</sub> ), expressed in W		4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	105	Spectral power dis-	See image		
sions without	Width	60	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	60		
		Chromaticity coordinates (x and y)	0,390 0,410		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	-10	Survival factor	0,90		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,1		

(a)'-': not applicable; (b)'-': not applicable;

