

Project: \_\_\_\_\_


Location: \_\_\_\_\_

Cat.No: \_\_\_\_\_

Type: \_\_\_\_\_

Lamps: \_\_\_\_\_ Qty: \_\_\_\_\_

Notes: \_\_\_\_\_



### Ordering Guide

Example: P1910 86 A T D

Product Code	P1910	
<b>Pole Height</b>	86	8' 6"
	106	10' 6"
	126	12' 6"
	146	14' 6"
<b>Finish</b>	A	Black
	B	White
	G	Verde
	H	Bronze
	I	Gray
	J	Green
<b>Outlet Location (Optional)</b>	T	12" Down from Top - Aligned with House Side
	B	4" Up from Top of Base - Aligned with House Side
<b>Outlet Options (Optional)</b>	D	Standard Duplex
	G	GFI Duplex

### Specifications

**HOUSING:**

356 HM high-strength, low-copper, proprietary cast aluminum alloy . 6063-T6 Extruded aluminum . Anchor rods are hot dipped galvanized steel .

**FINISH:**

A durable polyurethane enamel finish is applied after assemblies are shot blasted to create a surface profile which allows for the highest level of paint adhesion. Laboratory tested for superior weatherability and fade resistance in accordance with ASTM B-117-64 and ANSI/ASTM G53-77 specifications. For larger projects where a custom color is required, contact the factory for more information.

**WARRANTY:**

Three-year limited warranty.

**OUTLET:**

Standard Duplex Outlet has universal metal weatherproof cover. Weatherproof while in use. Heavy-duty all-metal construction. Lockable security cover. Meets NEC 406.9 (B). Weather resistant. GFI Duplex Outlet has dual-function indicator light, universal metal weatherproof cover. Weatherproof while in use. Heavy-duty all-metal construction. Lockable security cover. Meets NEC 406.9 (B). Weather resistant.

# P1910 P1910

## Pole

### Specifications

---

**Tenon/Top:**

3" OD

**Bolt Circle:**

7" x 9 1/2"

**Anchor Rods:**

(4) 3/4" dia. x 19"

**Base Dimensions:**

12 1/4 dia. x 20 3/4"

**Hand Hole :**

7 " x 9"

**Shaft:**

4" to 3" Tapered

**Wall Thickness:**

0.125 Aluminum

**Height :**

8' 6", 10' 6", 12' 6", 14' 6"

### Pole EPA Values

---

Windspeed(mph)	Height			
	8'	10'	12'	14'
80	12.6700	9.6700	7.5700	4.7900
100	7.8200	5.7900	4.3400	2.5800

