



Ledinaire All-in floodlights

BVP169 LED157/830_40_65 PSU 135W AWB PH

Ledinaire All-in floodlights, 135 W, 15000 lm, 15750 lm, 3000 K, 4000 K, 6500 K, CRI80, Asymmetrical, IP65

With this Ledinaire all-in floodlights range, you can easily adjust the color temperature by a simple switch. No need to choose between warm white, neutral white or cool white anymore, you get all these in one single product! The range comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General Information		Operating and Electrical	
Lamp family code	LED157-4S [LED module, system flux 15500 lm]	Luminous efficacy (rated) (nom.)	115 110 lm/W
Number of gear units	Unit	Colour rendering index (CRI)	>80
Driver included	Yes	Light source colour	Multi Colour Temperature
Light source engine type	LED system in flux	Optic type	Assymetric beam angle
Value ladder	Value	Luminaire light beam spread	92° x 52°
Serviceability class	Class C, luminaire without serviceable parts, not serviceable	Optic type outdoor	Asymmetrical
Warranty period	5 years	All-in Type	All-in, Multi Color Temperature
Sustainability rating	Unclassified	Effective projected area	0.07744 m²
Light Technical			
Upwards light output ratio	0	Input Voltage	220-240 V
Luminous Flux	15,000 15,750 lm	Line Frequency	50 or 60 Hz
Correlated Colour Temperature (Nom)	3000 4000 6500 K	Inrush current	7.8 A
		Inrush time	0.01520 ms
		Power Consumption	135 W
		Power Factor (Fraction)	0.95

Ledinaire All-in floodlights

Connection	Flying leads/cables
Cable	Cable 2.0 m without plug
Number of products on MCB (16 A type B)	14
Suitable for random switching	Not applicable
Protection class IEC	Safety class I
Surge Protection (Common/Differential)	Surge protection level until 1.5 kV differential mode and 1.5 kV common mode
Total harmonic distortion	20 %

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Driver integrated on LED board (DoB)
Constant light output	No
Photocell	Photocell included

Mechanical and Housing

Housing material	Aluminium die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Housing Colour	Grey
Mounting device	Via U Shaped Bracket, Aiming Scale Angle, Universal Installation
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	401 mm
Overall width	282 mm
Overall height	37 mm
Dimensions (height x width x depth)	37 x 282 x 401 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Standard tilt angle post-top	27°
Standard tilt angle side entry	-
Optical cover type	Glass
Net Weight (Piece)	3.210 kg

Emergency Operation

Central Emergency	No
-------------------	----

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
----------------	-----------------------------------

Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM)	1
Ambient temperature range	-25 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.440,0.403); (0.369,0.364); (0.313,0.337) SDCM<5
Power consumption tolerance	+/-10%
Init. Colour Rendering Index Tolerance	-2
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50,000 h	7.5 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L80
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	L70

Product Data

Order product name	BVP169 LED157/830_40_65 PSU 135W AWB PH
Full product name	BVP169 LED157/830_40_65 PSU 135W AWB PH
Full EOC	872016973641299
Order code	911401885586
Material no. (12 NC)	911401885586
Numerator – quantity per pack	1
EAN/UPC – Product/Case	8720169736412
Numerator – packs per outer box	4
EAN/UPC - Case	8720169736498

Ledinaire All-in floodlights

Dimensional drawing

