



# HF-Regulator II for PL-T/C

## HF-R 2 26-42 PL-T/C EII 220-240V 50/60Hz

Compact, lightweight High-Frequency electronic regulating ballast for PL-T and PL-C compact fluorescent lamps

### Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Earth leakage current (max.)	0.5 mA
Inrush current width	0.35 ms
Inrush current peak (max.)	45 A
Number of products on MCB (16 A type B) (nom.)	12
Wiring	
Connector type input terminals	Insert
Connector type output terminals	Insert
Temperature	
T-case lifetime (nom.)	65 °C
T-Case maximum (max.)	75 °C
Controls and Dimming	
Control interface	1-10V


Mechanical and Housing	
Housing	S 123x79x33
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	0.230 kg
Approval and Application	
Energy efficiency index	A1 BAT
Safety standard	IEC 61347-2-3
Environmental standard	ISO 14001
Approval marks	CE marking ENEC certificate VDE-EMV certificate
Ambient temperature range	-20°C to 50°C

Product Data	
Order product name	HF-R 2 26-42 PL-T/C EII 220-240V 50/60Hz
Full product name	HF-R 2 26-42 PL-T/C EII 220-240V 50/60Hz
Full EOC	872790080972500
Order code	80972500
Material no. (12 NC)	913700626566
Local order code	HFR226-42PLCT
Numerator – quantity per pack	1

# HF-Regulator II for PL-T/C

EAN/UPC — Product/Case	8711500880758
Numerator – packs per outer box	12
EAN/UPC - Case	8727900809725

## Dimensional drawing



Product	D1	C1	A1	A2	B1	B2
HF-R 2 26-42 PL-T/C EII 220-240V 50/60Hz	4.5 mm	33.0 mm	123.0 mm	111.0 mm	79.0 mm	67.0 mm

