



MasterConnect LEDspot GU10



MC LEDspot IA 4.7-50W GU10 940 36D

Introducing MasterConnect LED lamps – smart retrofit LED lamps that give you an easy and seamless way to upgrade to connected lighting. Simply set up with an intuitive app, MasterConnect LED lamps can be programmed to maximise energy savings, while providing wireless and automated light for your comfort and convenience. What's more, it is fully scalable and upgradable. If you want to enjoy further benefits, such as remote control or management dashboard, you can simply keep the currently installed lamps and add a gateway to experience all the advantages of a cloud-based system. There's no better way to take lighting solutions to the next level.


Product data

General Information			
Cap base	GU10	Colour rendering index (CRI)	90
Nominal lifetime	25,000 h	LLMF at end of nominal lifetime (nom.)	70 %
Switching Cycle	50,000	Luminous flux in 90° cone (rated)	345 lm
Lighting Technology	LED	Photobiological safety according to EN 62471	RG1
Flux measurement reference	Narrow Cone	Operating and Electrical	
Light Technical		Line Frequency	50 to 60 Hz
Colour Code	940 [CCT of 4000K]	Input frequency	50 to 60 Hz
Beam angle (nom.)	36 degree(s)	Power Consumption	4.7 W
Luminous Flux	345 lm	Lamp current (nom.)	27 mA
Luminous intensity (nom.)	500 cd	Starting time (nom.)	0.5 s
Colour designation	Cool White (CW)	Warm-up time to 60% light	0.5 s
Correlated Colour Temperature (Nom)	4000 K	Power Factor (Fraction)	0.7
Luminous efficacy (rated) (nom.)	73 lm/W	Voltage (nom.)	220-240 V
Colour consistency	<4	Inrush current at mains	2.2
		Max. lamp no. on MCB B type 10A — Mains	333

MasterConnect LEDspot GU10

Max. lamp no. on MCB B type 10A – EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 10A – EM ballast with Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A – Mains	533
Max. lamp no. on MCB B type 16A – EM ballast without Compensation Capacitor.	-
Max. lamp no. on MCB B type 16A – EM ballast with Compensation Capacitor.	-
Ballast Compatibility	Mains
Temperature	
T-Case maximum (nom.)	85 °C
Controls and Dimming	
Dimmable	Wireless Dim
Mechanical and Housing	
Lamp Finish	Frosted
Bulb material	Plastic
Product length	100 mm
Bulb shape	PAR16
Net Weight (Piece)	0.052 kg
Approval and Application	
Energy Efficiency Class	F

Dimensional drawing




Energy-saving product	Yes
Approval marks	RoHS compliance
Energy consumption kWh/1,000 hours	5 kWh
EPREL Registration Number	387345
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM)	0.5
Stroboscopic effect	0.1


Product Data	
Order product name	MC LEDspot IA 4.7-50W GU10 940 36D
Full product name	MC LEDspot IA 4.7-50W GU10 940 36D
Full EOC	871869969396100
Order code	929002253902
Material no. (12 NC)	929002253902
Local order code	MCLEDSPOT940
Numerator – quantity per pack	1
EAN/UPC – Product/Case	8718699693961
Numerator – packs per outer box	10
EAN/UPC - Case	8718699693978

Product	D	C
MC LEDspot IA 4.7-50W GU10 940 36D	50 mm	54 mm


Photometric data



Accent Lighting Spots - MC LEDspot IA 4.7-50W GU10 940 36D




Spectral Power Distribution Colour - MC LEDspot IA 4.7-50W GU10 940 36D




Light Distribution Diagram - MC LEDspot IA 4.7-50W GU10 940 36D

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - MC LEDspot IA 4.7-50W GU10 940 36D

MasterConnect LEDspot GU10

