



LED MR16

6.3MR16/LED/F25/927/D/EC/12V T20 10/1FB

Philips LED MR-16 lamps with single optic technology provide the look and color quality of traditional halogens while using a fraction of the energy. A perfect fit for spot lighting, they are compatible with most existing fixtures with MR16 GU5.3 holders and are designed as a retrofit replacement for halogen or incandescent spots.

Product data

General Information	
Cap-Base	GU5.3
Nominal lifetime	25,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Light Technical	
Color Code	927 [CCT of 2700K]
Beam Angle (Nom)	25 degree(s)
Luminous Flux	470 lm
Luminous Intensity (Nom)	1,960 cd
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	74.00 lm/W
Color Consistency	<3
Color rendering index (CRI)	91
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	6.3 W

Lamp Current (Nom)	600 mA
Wattage Equivalent	42 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	89 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Aluminum
Bulb Shape	MR16
UL Wet/ damp/ dry location	Damp location
Net Weight (Piece)	0.052 kg
Approval and Application	
Suitable For Accent Lighting	Yes

LED MR16

EU RoHS compliant	Yes
T20 compliant	Yes

Application Conditions


can it be used in closed luminaires	Yes
-------------------------------------	-----

Product Data

Order product name	6.3MR16/LED/F25/927/D/EC/12V T20 10/1FB
Full product name	6.3MR16/LED/F25/927/D/EC/12V T20 10/1FB


Order code	929003080304
Material Nr. (12NC)	929003080304
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677573539
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677573534

Dimensional drawing




Product	D	C
6.3MR16/LED/F25/927/D/EC/12V T20 10/1FB	50.5 mm	46 mm

Photometric data




Light Distribution Diagram - 6.3MR16/LED/F25/927/D/EC/12V T20 10/1FB



Spectral Power Distribution Colour - 6.3MR16/LED/F25/927/D/EC/12V T20 10/1FB

LED MR16


Photometric data




Technical Information 1.1 Philips Lighting B.V. Page 10

Accent Lighting Spots - 6.3MR16/LED/F25/927/D/EC/12V T20 10/1FB

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - 6.3MR16/LED/F25/927/D/EC/12V T20 10/1FB

