



Classic filament LEDbulbs

9.5A19/LED/930/FR/Glass/E26/DIM 1FB T20

Featuring a classic heritage design, Classic filament LEDbulbs combine the familiar shapes of classic incandescent bulbs with the benefits of the long lasting LED technology. They deliver beautiful, decorative warm-white light while saving around 90% on energy costs compared with traditional light bulbs.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	15,000 hour(s)
Switching Cycle	20,000
Lighting Technology	LED
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	320 degree(s)
Luminous Flux	1,100 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	115.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz

Power Consumption	9.5 W
Lamp Current (Nom)	80 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	120 V
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Glass
Bulb Shape	A19
UL Wet/ damp/ dry location	Wet location
Net Weight (Piece)	0.033 kg
Approval and Application	
EU RoHS compliant	Yes

Classic filament LEDbulbs

T20 compliant	Yes
Ambient temperature range	-20 °C to 45 °C

Application Conditions


can it be used in closed luminaires	Yes
-------------------------------------	-----

Product Data

Order product name	9.5A19/LED/930/FR/Glass/E26/DIM 1FB T20
Full product name	9.5A19/LED/930/FR/Glass/E26/DIM 1FB T20


Order code	929003498004
Material Nr. (12NC)	929003498004
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677578596
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677578591

Dimensional drawing




Product	D	C
9.5A19/LED/930/FR/Glass/E26/DIM 1FB T20	60 mm	105 mm

Photometric data




Light Distribution Diagram - 9.5A19/LED/930/FR/Glass/E26/DIM 1FB T20



General uniform lighting - 9.5A19/LED/930/FR/Glass/E26/DIM 1FB T20


Classic filament LEDbulbs

Photometric data




Spectral Power Distribution Colour - 9.5A19/LED/930/FR/Glass/E26/DIM 1FB T20

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - 9.5A19/LED/930/FR/Glass/E26/DIM 1FB T20

