

The background of the advertisement is a modern office interior. It features long, sleek, white linear light fixtures mounted on the ceiling, which illuminate a workspace with white desks and light-colored wood-grain paneling. Several ergonomic office chairs are positioned at the desks. Large windows with horizontal blinds are visible in the background, allowing natural light to complement the artificial lighting. The overall aesthetic is clean, professional, and futuristic.

PHILIPS

TrueLine Elite



Smart



Scalable



Sustainable

interact ready.

Future ready your
business with **smart
office lighting**

The right luminaire for every space



The TrueLine family offers various mounting options; suspended, surface-mounted and recessed. It can be used as a standalone individual luminaire or as a continuous line of light. You can also choose to apply direct or indirect lighting, depending on the space and its purpose. The range's excellent design uniformity is maintained across all standard and specifically tailored lighting solutions.

CRI90, SDCM3 are standard with TrueLine family and support designing for health and well-being as defined by the **WELL Building Standard**.

Lighting controls play an important part in providing complete office lighting systems. Signify is able to offer 'Interact Office' connected lighting in both wired and wireless solutions as well as the user friendly 'Spacewise' system. More details on page 6.

- ✓ High quality CRI90 LED chips with SDCM 3 specification ensure the best colour quality and minimal colour shift
- ✓ Various lumen output options allow for total flexibility in the design in process
- ✓ Multiple choices of control interfaces are available to make lighting control simple
- ✓ Multiple lengths 0.6m, 1.2m, 1.5m and 2.4m

• Up to 150lm/W Efficacy

• L75 @ 100,000hrs
• L80 @ 70,000hrs
• L85 @ 50,000hrs

• Dali/Interact Ready
System Ready

• CRI 90 / R9 >50

• Surface / Suspended
& Recessed mount

• Standalone or
continuous line

Meeting Room Lighting



Silo Office Lighting



Specifications – Trueline Elite Extrusion

MODEL	SP530P & SP531P Suspended (Direct) & SM530C Surface							
Type	LED15	LED25	LED34	LED40	LED19	LED31	LED43	LED50
Power (PSD)	10W	18W	24W	28W	12W	22W	28W	34W
System Lumens	1500lm	2500lm	3400lm	4000lm	1900lm	3100lm	4300lm	5000lm
System Efficacy	150lm/W	139lm/W	141lm/W	142lm/W	158lm/W	141lm/W	153lm/W	147lm/W
Size*	1130mm				1410mm			

MODEL	SP532P Suspended (Direct-Indirect)							
Type	LED21	LED36	LED49	LED58	LED29	LED47	LED66	LED77
Power (PSD)	15W	25W	36W	41W	19W	32W	46W	56W
System Lumens	1500/660lm	2500/1100lm	3400/1550lm	4000/1850lm	1900/1000lm	3100/1650lm	4300/2300lm	5000/2700lm
System Efficacy	144lm/W	144lm/W	138lm/W	143lm/W	152lm/W	147lm/W	143lm/W	138lm/W
Size*	1130mm				1410mm			

MODEL	SP533P Suspended (Direct-Indirect)							
Type	LED24	LED41			LED33	LED54		
Power (PSD)	21W	36W			29W	51W		
System Lumens	1500/940	2500/1600			1900/1400	3100/2300		
System Efficacy	116lm/W	114lm/W			114lm/W	106lm/W		
Size*	1130mm				1410mm			

MODEL	Trueline Elite Extrusion (Recessed) RC530B/RC531B/RC533B/RC533B							
Type	LED15	LED25	LED34	LED40	LED19	LED31	LED43	LED50
Power (PSD)	10W	18W	24W	28W	12W	22W	28W	34W
System Lumens	1500lm	2500lm	3400lm	4000lm	1900lm	3100lm	4300lm	5000lm
System Efficacy	150lm/W	139lm/W	141lm/W	142lm/W	158lm/W	141lm/W	153lm/W	147lm/W
Size*	VPC (Visible Profile Ceiling) 1197mm, PCV (Plaster Ceiling) 1152mm				VPC (Visible Profile Ceiling) 1497mm, PCV (Plaster Ceiling) 1432mm			

GENERAL	
Colour Temperature	3000K & 4000K
Mounting	Standalone & Continuous line with line end & line feature connection, Suspended option supplied with wires & ceiling connection box
Input Voltage	220-240V
Electrical Class	I
Driver Type	PSD-Dali /System Ready
Electrical Connection	1.5m 5 core pre-wired flex for suspended option only, PIP (Push-In -Connection) for surface & recessed mount
Lumen Maintenance***	100,000hrs L75, 70,000 L80, 50,000 L85 @ 25°C
SDCM	3
CRI	CRI90 (R9 is equal to or greater than 50)
IP Rating	IP40/IP20 for IAO & SWZ
UGR Rating**	UGR19
Material	Aluminium Frame, PMMA frosted front lens
Finish	Black (RAL9004), White (RAL 9003) & Aluminium Finish
Warranty	5 Years

0.6m, 1.8m & 2.4m lengths available on request. * Size for stand-alone PSD models. ** For 530 & 532 models. *** Based on TM21 Calculated lumen maintenance.

Lobby Lighting



Flicker free

Philips Office Elite Products utilise industry best LED drivers that deliver flicker¹ free performance and no stroboscopic effect².


¹ Additionally the Dali standard specifies 8 bit (256 discrete light levels) that can introduce the appearance of Flicker during transitions (dynamic dimming). Dimming performance is improved with Elite Luminaires by the addition of further bits totalling 32,000 (15bit). These interpolated dimming levels protect against flicker artefact's during light level transitions.

² In the absence of compulsory standards Philips Lighting opted to use the accepted test methods according to IEC TR 61547-1 [1] (Flicker) and IEC TR 61547-1 [5] (Stroboscopic Effect) with the following limits: PstLM ≤ 0.5 and SVM ≤ 1.

Polar intensity


TrueLine Suspended

Office compliant
SP530P




direct

Office compliant
SP532P




direct / indirect

Wide Beam
SP531P



direct


Wide Beam
SP533P



direct / indirect


TrueLine Surface - Mounted

Office compliant
SM530C



direct

Wide Beam
SM531C



direct


Asymmetrical
SM531C



direct


TrueLine Recessed

Office compliant
RC530B/RC532B




direct

Non-Office compliant
RC531B/RC533B



direct

Asymmetrical



How to create uniform continuous lines of light

To build a uniform line of light, we need to connect more modules:


Surface & Suspended (PSD models)

Add 1 pcs of Line End (LE1) to a/many Line Features (LF1). No other components are required (these are included in the LE1)

Examples for Suspended/Surface mounted luminaires

6 luminaires	8 luminaires
1pcs of LE1	1pcs of LE1
5pcs of LF1	7pcs of LF1


The maximum number of luminaires in a line for both the 1.2m and 1.5m = 10, however you can now add an 11th piece with additional cable which will allow another 10pcs and so on.



Recessed (PSD Models)

Add 2 standard fixtures (RC532B) and 1 set of end caps (RC530Z EP WH) which needs to be ordered separately.

First luminaire in a line



Examples for Recessed mounted luminaires

4pcs of RC532B (coupling features are included) 1 set of RC530Z EP WH (End Caps) Max number of luminaires in a line for both the 1.2m and the 1.5m is : 16





Control Options

Dali A reliable constant current Dali Driver is supplied standard with the Trueline luminaires to provide stable lumen output and light quality that lighting specifiers and architects demand. The dimming range is between 1-100% and the driver interfaces with DALI and Touch & Dim control systems.

Lighting control made easy with Dynalite The Philips Dynalite control platform benefits from 30 years of experience in delivering superior lighting control solutions. Dynalite manages all DALI luminaires, Tunable White recipes to create better environments, and occupancy strategies to maximise the efficiency of workspaces. This takes place seamlessly through multiple control components and the distributed intelligence defining relationships within the system architecture. Reporting and monitoring of the network via Dynalite System Manager software not only provides insights into the operation but also DALI reporting – giving the client the necessary tools to effectively manage the intelligent building.

Get more out of your Luminaire with SpaceWise Controllable wireless lighting gives you the flexibility to set the right lighting level for each specific area within your office space, while also allowing workers to personalise their own settings, thereby enhancing their well-being and comfort. You can achieve all these goals while making significant savings. Philips SpaceWise gives you all the flexibility you need and installation is easy. There is no need for expensive and complicated rewiring. Integrated sensors in every luminaire allows for full occupancy sensing and daylight harvesting. The ZigBee Drivers will communicate with all other luminaires wirelessly. Programming and Zoning is achieved via a remote control.

Turn your **working** environment into a **smart office**





interact
Office

Support employee performance and reduce time wasted with the Interact Office software and system architecture. This will help employees find free meeting rooms or an available workspace, and enable them to personalise lighting. Then use occupancy insights to see where and how people prefer to work, opening your eyes to potential for energy and space savings, and efficiency gains. Simply install LED connected lighting from Philips with embedded IoT sensors, and use Interact Office software and insights to increase building efficiency and optimize space to create a sustainable smart office. Available in both wired (POE) and Wireless options.









Dimensions

Dimensions shown below are nominal measurements. Slight variations in dimensions may occur in production.

TrueLine surface-mounted, stand-alone SM530C, SM531C



TrueLine surface-mounted, continuous SM530C, SM531C




Dimensions

Dimensions shown below are nominal measurements. Slight variations in dimensions may occur in production.

TrueLine suspended, stand-alone, SP530P, SP531P, SP532P, SP533P


L1130

PSD Option




L1170


System Ready Option



L1410




L1450



TrueLine suspended, continuous, SP530P, SP531P, SP532P, SP533P


Line End LE1, 1130

PSD Option




Line End LE1, 1170

System Ready Option




Line Feature LF1, 1130




Line Feature LF1, 1170




Line End LE1, 1410



Line End LE1, 1450



Line Feature LF1, 1410




Line Feature LF1, 1450



Dimensions

Dimensions shown below are nominal measurements. Slight variations in dimensions may occur in production.

TrueLine Recessed, RC530B





office
compliant



wide beam



asymmetrical version

Suspended

Optic	Distribution	Flux (LED)	Length	Colour Temp	Driver	Wiring	Suspension Set	Line Version	Colour
Office Compliant	Direct (SP530P)	1500 (15S)	L1130/L1170*	3000 (930) 4000 (940)	PSD (Dali) SWZ (Spacewise) IAO (Interact Office)	P15 (Push-in connection)	SM2	Stand-alone Continuous Line-end (LE) Continuous Line-feature (LF)	ALU (Aluminium) WH (RAL9003) BK (RAL 9004)
		2500 (25S)							
		3400 (34S)							
		4000 (40S)							
		1900 (19S)	L1410/L1450*						
		3100 (31S)							
		4300 (43S)							
		5000 (50S)							
	Direct/Indirect (SP532P)	2160 (21S)	L1130/L1170*						
		3600 (36S)							
		4950 (49S)							
		5850 (58S)							
		2900 (29S)	L1410/L1450*						
		4750 (47S)							
6600 (66S)									
7700 (77S)									
Wide Beam	Direct (SP531P)	1500 (15S)	L1130/L1170*						
		2500 (25S)							
		1900 (19S)	L1410/L1450*						
		3100 (31S)							
	Direct/Indirect (SP533P)	2440 (24S)	L1130/L1170*						
		4100 (41S)							
		3300 (33S)	L1410/L1450*						

Standard Code Examples

SP530P LED34S/940 PSD PI5 SM2 L1130 ALU	SP531P LED25S/940 PSD PI5 SM2 L1130 ALU
SP530P LED43S/940 PSD PI5 SM2 L1410 ALU	SP531P LED31S/940 PSD PI5 SM2 L1410 ALU
SP532P LED36S/940 PSD PI5 SM2 L1130 ALU	SP533P LED41S/940 PSD PI5 SM2 L1130 ALU
SP532P LED47S/940 PSD PI5 SM2 L1410 ALU	SP533P LED54S/940 PSD PI5 SM2 L1410 ALU
SP532P LED49S/940 PSD PI5 SM2 L1130 ALU	
SP532P LED66S/940 PSD PI5 SM2 L1410 ALU	

Surface Mounted

Optic	Distribution	Flux (LED)	Length	Colour Temp	Driver	Wiring	Suspension Set	Line Version	Colour
Office Compliant	Direct (SM530C)	1500 (15S)	L1130/L1170*	3000 (930) 4000 (940)	PSD (Dali) SWZ (Spacewise) IAO (Interact Office)	P15 (Push-in connection)	N/A	Stand-alone	ALU (Aluminium)
		2500 (25S)							
		3400 (34S)							
		4000 (40S)							
		1900 (19S)	L1410/L1450*						
		3100 (31S)							
		4300 (43S)							
5000 (50S)									
Wide Beam	Direct (SM531C)	1500 (15S)	L1130/L1170*						
		2500 (25S)	L1410/L1450*						
		1900 (19S)							
		3100 (31S)							

* Dimensions for types with Sensors

Standard Code Examples

SM530C LED34S/940 PSD PI5 L1130 ALU	SM530C LED43S/940 PSD PI5 L1410 ALU	SM531C LED25S/940 PSD PI5 L1130 ALU
SM530C LED40S/940 PSD PI5 L1130 ALU	SM530C LED50S/940 PSD PI5 L1410 ALU	SM531C LED31S/940 PSD PI5 L1410 ALU

Recessed Stand-alone

Optic	Distribution	Flux (LED)	Length	Colour Temp	Driver	Wiring	Colour
Office Compliant	Direct (RC530B)	1500 (15S)	Plaster Ceiling Variant (PCV) L1152 Visable Profile Variant (VPC) L1197	3000 (930) 4000 (940)	PSD (Dali)	P15 (Push-in connection)	WH (RAL9003)
		2500 (25S)					
		3400 (34S)					
		4000 (40S)					
		1900 (19S)	Plaster Ceiling Variant (PCV) L1432 Visable Profile Variant (VPC) L1497				
		3100 (31S)					
		4300 (43S)					
Wide Beam	Direct (RC531B)	5000 (50S)	Plaster Ceiling Variant (PCV) L1152 Visable Profile Variant (VPC) L1197 Plaster Ceiling Variant (PCV) L1432 Visable Profile Variant (VPC) L1497				
		1500 (15S)					
		2500 (25S)					
		1900 (19S)					
		3100 (31S)					

Recessed Line Continuous

Optic	Distribution	Flux (LED)	Length	Colour Temp	Driver	Wiring	Colour		
Office Compliant	Direct (RC532B)	1500 (15S)	(VPC/PCV) L1127	3000 (930) 4000 (940)	PSD (Dali)	P15 (Push-in connection)	WH (RAL9003)		
		2500 (25S)							
		3400 (34S)							
		4000 (40S)							
		1900 (19S)	(VPC/PCV) L1408						
		3100 (31S)							
		4300 (43S)							
5000 (50S)									
Wide Beam	Direct (RC533B)	1500 (15S)	(VPC/PCV) L1127						
		2500 (25S)	(VPC/PCV) L1408						
		1900 (19S)							
		3100 (31S)							

Standard Code Examples

RC530B LED34S/940 PSD W8L113 PCV PI5	RC532B LED34S/940 PSD W8L113 PCV PI5
RC530B LED40S/940 PSD W8L113 PCV PI5	RC532B LED40S/940 PSD W8L113 PCV PI5
RC530B LED43S/940 PSD W8L141 PCV PI5	RC532B LED43S/940 PSD W8L141 PCV PI5
RC530B LED50S/940 PSD W8L141 PCV PI5	RC532B LED50S/940 PSD W8L141 PCV PI5
RC531B LED25S/940 PSD W8L113 PCV PI5	RC533B LED25S/940 PSD W8L113 PCV PI5
RC531B LED31S/940 PSD W8L141 PCV PI5	RC533B LED31S/940 PSD W8L141 PCV PI5



© 2020 Signify Holding. All rights reserved. Signify reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication. Application images shown may not reflect actual products advertised.

Version: August 2020

Signify New Zealand Limited

Level 3, 123 Carlton Gore Road
Newmarket, Auckland 1023
New Zealand
T: 0800 454 448 / 0800 4 LIGHT

lighting.philips.co.nz

Signify Australia Limited

65 Epping Road, North Ryde
NSW 2113
Australia
T: 1300 110 500

philips.com.au/lighting