



Philips GreenPower LED Interlighting 3.3

Length	2.0 m 1.95 m • 76.7 in	2.5 m 2.42 m • 95.3 in	Input voltage	200 – 400V	Ambient operating temp	0° C Min. • 40° C Max
Width	6.5 cm • 2.6 in	6.5 cm • 2.6 in	Beam angle	Bi-directional 120°	Frequency	32° F Min. • 104° F Max
Height	7.6 cm • 3.0 in	7.6 cm • 3.0 in	Q90	> 36,000 hrs	Power factor	50/60 Hz
Weight	2.2 kg • 4.9 lb	2.5 kg • 5.5 lb	Warranty	5 year limited	Total harmonic distortion	> 0.90
			UL/CSA rated	Damp/wet		< 10%
			IP rating	IP66		

High Output (HO) 200 – 400V

Description	12 NC	Power (W)	Amps 208V	Amps 240V	Amps 277V	Amps 347V	Photon Flux µmol/s	Efficacy µmol/J
GPL IL 300 DRB L250 200-400V 3.3S	9290 039 65190	80	0.38	0.33	0.29	0.23	300	3.8
GPL IL 240 DRB L200 200-400V 3.3S	9290 039 65167	64	0.31	0.27	0.23	0.18	240	3.8

Extra High Output (EHO) 277 – 400V

Description	12 NC	Power (W)	Amps 277V	Amps 347V	Photon Flux µmol/s	Efficacy µmol/J
GPL IL 440 DRB L250 277-400V 3.3S	9290 039 65191	117	0.42	0.34	440	3.8
GPL IL 350 DRB L200 277-400V 3.3S	9290 039 65193	94	0.34	0.27	350	3.7